



XS Series 1-Pole Tumbler Switch Cover With Device - 20A

By Killark
Catalog # [XS-1C](#)

XS Series - Aluminum 1-Pole Tumbler Switch Cover With Device - 20A



Features

- Front lever rotary operated switch assemblies.
- Standard provisions for padlocking in either “ON” or “OFF” position.
- The lever is connected to a threaded stainless steel shaft which passes through the cover.

Application

Used where making, breaking, or changing connections in an electric circuit is required.

Specifications

CSA File Number	LR11712
EU RoHS Indicator	Contact Manufacturer
UL File Number	E53360
Hazardous Rating(s)	• Class I, Divisions 1 & 2, Groups C, D • Class I, Zones 1 & 2, Groups IIB, IIA • Class II, Divisions 1 & 2, Groups E, F, G • Class III, Divisions 1 & 2

Conductor

Number Of Poles	1
-----------------	---

Configuration

Back Box Type	SWB
---------------	-----

Current

Frequency Rating	50/60 Hz
Amperage Rating	20 A

Dimensions

Length	3.5 in
Depth	4-1/4 in
Weight	1.098 lb.
Height	3.25 in
Width	7.875 in
Gross Weight with Packaging	1.098
Dimensions	3.5 in x 7.875 in x 3.25 in

General

Color	Gray
Series	XS Series
UPC	783936925004
Type	Aluminum Tumbler Switch Cover
Material	Aluminum, Copper Free (less than 4/10 of 1%)

Operational

Actuator	Lever
Action	SPST

Product Assets

[Installation Manual \[French, English\]](#)