KILLARK®

XS Series - Feed-Thru Box And Cover With 2-Pole Tumbler Switch- Conduit Hub Size 1/2 In - 20 Amps

By Killark
Catalog # XS-42C

XS Series - Aluminum Feed-Thru Box And Cover With 2-Pole Tumbler Switch- Conduit Hub Size 1/2 In - 20 Amps

Features

- Front lever rotary operated switch assemblies.
- Standard provisions for padlocking in either “ON” or “OFF” position.
- The lever is connected to a threaded stainless steel shaft which passes through the cover.

Application

Used where making, breaking, or changing connections in an electric circuit is required.

Specifications

UL File Number	E53360
Buy America(n) Qualified	Contact Manufacturer
CSA File Number	LR11712
Hazardous Rating(s)	• Class I, Divisions 1 & 2, Groups C, D • Class I, Zones 1 & 2, Groups IIB, IIA • Class II, Divisions 1 & 2, Groups E, F, G • Class III, Divisions 1 & 2
EU RoHS Indicator	Contact Manufacturer

Conductor

Number Of Poles	2

Configuration

Back Box Type	SWB

Current

Frequency Rating	50/60 Hz
Amperage Rating	20 A

Dimensions

Gross Weight with Packaging	2.4
Depth	4-1/4 in

General

Color	Gray
UPC	783936930466
Type	Aluminum Tumbler Switch Box And Cover
Series	XS Series

Operational

Actuator	Lever
Action	DP

Product Assets

Catalog [English]

© 2026 Hubbell Incorporated. All rights reserved