KILLARK®

XST Series - Feed-Thru 1-Pole Tumbler Switch Unit - Hub Size 3/4 Inch - 347VAC/20A

By Killark
Catalog # XST20-51C

XST Series - Aluminum Feed-Thru 1-Pole Tumbler Switch Unit - Hub Size 3/4 Inch - 347VAC/20A

Features

- Front lever rotary operated switch assemblies.
- Standard provisions for padlocking in either “ON” or “OFF” position.
- The lever is connected to a threaded stainless steel shaft which passes through the cover.

Application

Used where making, breaking, or changing connections in an electric circuit is required.

Specifications

Buy America(n) Qualified	Contact Manufacturer
CSA File Number	LR11712
Hazardous Rating(s)	• Class I, Divisions 1 & 2, Groups C, D • Class I, Zones 1 & 2, Groups IIB, IIA • Class II, Divisions 1 & 2, Groups E, F, G • Class III, Divisions 1 & 2
EU RoHS Indicator	Contact Manufacturer

Conductor

Number Of Poles	1

Configuration

Back Box Type	SWB

Current

Frequency Rating	50/60 Hz
Amperage Rating	20 A

Dimensions

Height	4.25 in
Width	5.75 in
Length	6.25 in
Gross Weight with Packaging	2.5
Depth	4-1/4 in
Dimensions	6.25 in x 5.75 in x 4.25 in

General

Color	Gray
UPC	783936075525
Type	Aluminum Tumbler Switch Box And Cover
Series	XST Series

Operational

Actuator	Lever
Action	SP

Product Assets

Catalog [English]
Installation Manual [French, English]

© 2026 Hubbell Incorporated. All rights reserved