KILLARK®

XSX-52 - XSD/XSX/FXSD/FXSX Series - XSX Single Gang Aluminum Manual Motor Starting Switch - 2 Pole 1 Phase - Feed-Thru - Hub Size 3/4 In

By Killark
Catalog # XSX-52

XSD/XSX/FXSD/FXSX Series - XSX Single Gang Aluminum Manual Motor Starting Switch - 2 Pole 1 Phase - Feed-Thru - Hub Size 3/4 In

Features

- XSX Series (without overload protection) are ideally suited for across the-line applications where a positive disconnect means is required.
- Enclosures are cast copper-free aluminum alloy.
- Operating shaft is stainless steel.
- Multiple gang assemblies available in combination with pilot lights, pushbuttons and switches on request.
- Ground flange joint between bolted cover and box provide required flame path.
- Provisions for padlocking switch in either “ON” or ”OFF” position is standard.

Application

Provides manual starting and stopping of small AC or DC motors. Motor running protection when overload heaters are used. XSX Series (without overload protection) is ideally suited for across-the-line applications where a positive disconnect means is requi

Specifications

Buy America(n) Qualified	Contact Manufacturer
CSA File Number	LR11714
Hazardous Rating(s)	• Class I, Divisions 1 & 2, Groups C, D • Class I, Zones 1 & 2, Groups IIB, IIA • Class II, Divisions 1 & 2, Groups E, F, G • Class III, Divisions 1 & 2
EU RoHS Indicator	Contact Manufacturer

Current

Power Factor	0.9
Frequency Rating	60 Hz
Voltage Rating	600 V

Dimensions

Height	5.5 in
Width	3.75 in
Length	6.88 in
Gross Weight with Packaging	2.4
Dimensions	6.88 in x 3.75 in x 5.5 in

General

UPC	783936933504
Type	Aluminum Manual Motor Starting Switch Without Overload Protection
Material	Copper-free aluminum
Series	XSX Series

Operational

Horsepower - Maximum	3

Product Assets

Catalog [English]
Catalog Page [English]

© 2026 Hubbell Incorporated. All rights reserved