KILLARK®

Y-2-EX - 90° 3/4″ Aluminum, Capped Elbow (Quad Listed)

By Killark
Catalog # Y-2-EX

90° 3/4″ Aluminum, Capped Elbow (Quad Listed)

Features

- Threaded for rigid conduit or IMC
- Smooth integral bushings to prevent damage to wires
- Certified QUAD listed

Application

To change direction 90° in rigid or IMC conduit systems where space is limited and access is needed for pulling conductors or maintenance.

Specifications

ATEX File Number	ITS09ATEX16417U
CSA File Number	LR11716
IECEx File Number	IECExITS09.0024U
EU RoHS Indicator	Contact Manufacturer
UL File Number	E10514
Hazardous Rating(s)	• II2G • Ex d IIC

Dimensions

Hub Size	3/4″
Length	4 in
Height	4 in
Width	3 in
Gross Weight with Packaging	0.27
Dimensions	4 in x 3 in x 4 in

General

Color	Gray
Series	Y Series
UPC	783936072289
Type	Capped Elbow
Material	Aluminum, Copper Free (less than 4/10 of 1%)
Cover Type	Threaded
Finish Type	Powder Epoxy Paint

Logistics

Carton Quantity	5

Product Assets

Installation Manual [English]

© 2026 Hubbell Incorporated. All rights reserved