



ZS312CR-EX-MG - 1" Nylon Cord Connector, Straight w/ Mesh Grip, Cord Range .875-1.000, Gray

By Killark
Catalog # [ZS312CR-EX-MG](#)

1" Nylon Cord Connector, Straight w/ Mesh Grip, Cord Range .875-1.000, Gray

Features

- Nylon retention ring for increased holding power
- Neoprene bushing seals against moisture
- Nylon connectors obtain approximately the same retention values as metal cord connectors
- Stainless steel mesh grips resist corrosion, prevent cord pull-out and control arc-of-bend

Application

Durable nylon construction makes these connectors perfectly suited to corrosive environments. Typical applications for nylon cord connectors include food processing facilities, chemical and sewage treatment plants, and off-shore and dockside installations

Specifications

UL File Number	E22698
Buy America(n) Qualified	Contact Manufacturer
CSA File Number	LR73478
Hazardous Rating(s)	Suitable for use in hazardous location applications when installed according to NEC Articles 501.10(b) (Class I, Division 2) or 502.10, 503.10, and 505.15 (Class I Zone 2).
EU RoHS Indicator	Contact Manufacturer

Conductor



Cable Range .875 - 1.000 in

Current

Power Factor	0.9
Frequency Rating	60 Hz

Dimensions

Height	2 in
Width	1 in
Hub Size	1"
Length	2 in
Gross Weight with Packaging	0.2
Dimensions	2 in x 1 in x 2 in

General

Color	Black, Gray
Color Code	Gray
Cord Range	.875-1.000,
UPC	783936996622
Type	Straight Cord Connector With Mesh Grip
Material	Nylon
Finish Type	Natural
Series	Z-EX Series

Product Assets

[Catalog \[English\]](#)