KILLARK®

ZS520-EX - 1-1/2″ Aluminum Cord Connector, Cord Range 1.750- 1.875,

By Killark
Catalog # ZS520-EX

1-1/2″ Aluminum Cord Connector, Cord Range 1.750- 1.875,

Features

- Aluminum construction resists corrosion
- Neoprene grommet seals out oil and moisture
- Nylon retention ring ensures superior holding power

Specifications

CSA File Number	LR73478
EU RoHS Indicator	Contact Manufacturer
UL File Number	E22698
Buy America(n) Qualified	Contact Manufacturer
Hazardous Rating(s)	Suitable for use in hazardous location applications when installed according to NEC Articles 501.10(b) (Class I, Division 2) or 502.10, 503.10, and 505.15 (Class I Zone 2).

Conductor

Cable Range	1.750 - 1.875 in

Dimensions

Hub Size	1-1/2″
Length	3 in
Height	2.2 in
Width	0.75 in
Gross Weight with Packaging	1
Dimensions	3 in x 0.75 in x 2.2 in

General

Color	Silver
Cord Range	1.750- 1.875,
Series	Z-EX Series
UPC	783936973029
Type	Straight Cord Connector
Material	Aluminum, Copper Free (less than 4/10 of 1%)
Finish Type	Natural

Logistics

Carton Quantity	2

Product Assets

Catalog [English]

© 2026 Hubbell Incorporated. All rights reserved