



2000A AC/DC Auto-Ranging TRMS Clamp Meter with Worklight



Klein Tools High Voltage Digital Clamp Meter is a professional-grade clamp meter engineered for extreme high-voltage applications up to 2000V and 2000A. It features TRMS auto-ranging accuracy, integrated worklight, and superior backlit display and is perfect for solar panel installations, wind turbines, and power distribution networks. Hands-free operation with test lead holder and magnetic hanger compatibility for safe, efficient renewable energy work.

Specifications

Type:	CAT IV Clamp Meter	Application:	Variety of Electrical Diagnostic and Troubleshooting Applications
Special Features:	Transflective Reverse-Contract Display; Lighted Dial; Built-in Worklight; Built-in Lead Holder	Material:	ABS
Batteries:	2 x AA	Battery Life:	40 hr
Auto-Power Off:	Yes	Jaw Size (Inch):	2
Jaw Size (cm):	5.1	Drop Protection:	6.6' (2 m)
Display:	Backlit Reverse-Contrast with 6000 Count LCD	Functions:	AC/DC Voltage, AC/DC Current, Resistance, DC Micro Amps, Audible Continuity, Temperature, Low Impedance, Non-Contact Voltage Testing, Diode Test, Capacitance, Frequency/Duty Cycle, Inrush, Min/Max Value, Rel/Zero, Data Hold Capability
Auto Ranging:	Yes	TRMS:	Yes
Voltage:	2000V AC; 2000V DC	Frequency:	10Hz-60kHz
Current:	2000A, AC/DC	Capacitance:	6000μF
Ohms (Resistance):	60M?	AC Voltage:	2000V
DC Voltage:	2000V	DC Polarity Indicator:	Yes
DC Micro-Amp:	200μA	Temperature Range:	-14° to 1000° F (-26° to 538° C)
Ingress Protection:	IP40	Accuracy:	See Instructions
Standard:	CAT IV 600V, CAT III 2000V, Class 2, Double Insulation, CE, UKCA	Included:	Clamp Meter; Right-Angle Input Test Leads; Thermocouple; Carrying Case; Instruction Manual; 2 x AA Batteries
Overall Length (Inch):	4.32	Overall Length (cm):	11
Overall Height (Inch):	11.37	Overall Height (cm):	28.9
Overall Width (Inch):	1.98	Overall Width (cm):	5
Weight (oz):	20.7	Weight (g):	587