

Browse Catalog

- Ballasts
- Compact Fluorescent
- Fluorescent
- Halogen
- High Intensity Discharge (HID)
- Incandescent
- Lampholders/Sockets
- Smart Connected Light
- LED Lamps
- LED Luminaires & Retrofit Kits
- LED Modules
- LED Power Supplies

[Return to Search](#)

[Print Page](#)



Product Number: 65768

Order Abbreviation: AREAFLD4A/S290UNVD840/T5/BZ

General Description: AREA FLOOD 4A, SELECTABLE WATTAGE 240W/270W/290W, 120-277V, 0-10V DIM, 80+ CRI, 4000K, T5 DISTRIBUTION, BRONZE

Product Information

Power Factor	≥0.90
Primary Lamp Type 1	SMD
Total Harmonic Distortion (THD)	< 20 %
Efficacy (LPW)	135 lm/W
Operating Voltage (V)	120
Power (W)	120
Abbrev. With Packaging Info.	AREAFLD4AS290UNVD840T5BZ 1/CS 1/SKU
Color Temperature/CCT (K)	4000
Ordering Abbreviation	AREAFLD4A/S290UNVD840/T5/BZ
Average Rated Life 1 (hr)	130000
Nominal Voltage (V)	120.00
Nominal Wattage (W)	290.00
Color Rendering Index (CRI)	80
Service Life Rating	130000
Lumens (lm)	33500 ... 40000 lm
Wattage (W)	290.00 W
Color Range	4000 K
Connectors	not relevant
Fixture Warranty	10 years
Housing	Aluminum
Luminaire Finish	Bronze
Luminaire Type	Area light
Maximum Operating Temperature-Celsius	40
Mounting	Surface
Certification Listing	RoHS FCC CE UL