



LED BR30

8.8BR30/CNG/827/FR/P/E26/DIM/120V 6/1CT

Contractor grade, LED, BR30, 65 W, E26 | Single Contact Medium Screw, 2700 K, 650 lm, 15000 hour(s), Plastic

Philips BR30 LED lamps are the smart alternative to standard incandescent. The traditional lamp design can provide excellent dimming performance with spectacular energy savings. They provide the beautiful light and dependable performance you expect from LED at an economical price.

Product data


General Information		Input Frequency	
Cap-Base	E26 [Single Contact Medium Screw]	Power Consumption	8.8 W
Nominal lifetime	15,000 hour(s)	Lamp Current (Nom)	90 mA
Switching Cycle	50,000	Wattage Equivalent	65 W
Lighting Technology	LED	Starting Time (Nom)	0.5 s
Light Technical		Warm-up time to 60% light	0.5 s
Color Code	827 [CCT of 2700K]	Power Factor (Fraction)	0.7
Beam Angle (Nom)	110 degree(s)	Voltage (Nom)	120 V
Luminous Flux	650 lm	UL Type	Yes
Color Designation	Warm White (WW)	Temperature	
Correlated Color Temperature (Nom)	2700 K	T-Case Maximum (Nom)	158 °F
Luminous Efficacy (rated) (Nom)	73 lm/W	Controls and Dimming	
Color Consistency	6DSCM	Dimmable	Only with specific dimmers
Color rendering index (CRI)	80	Mechanical and Housing	
LLMF At End Of Nominal Lifetime (Nom)	70 %	Bulb Finish	Frosted
Operating and Electrical		Bulb Material	Plastic
Line Frequency	60 Hz		

LED BR30

Bulb Shape	BR30
UL Wet/ damp/ dry location	Damp location
Net Weight (Piece)	0.148 lb
Approval and Application	
EU RoHS compliant	Yes
T20 compliant	No
Ambient temperature range	-4 °F to 113 °F
Application Conditions	
can it be used in closed luminaires	Yes



Product Data	
Order product name	8.8BR30/CNG/827/FR/P/E26/DIM/120V 6/1CT
Full product name	8.8BR30/CNG/827/FR/P/E26/DIM/120V 6/1CT
Order code	583583
Material Nr. (12NC)	929003619804
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	046677583583
Numerator - Packs per outer box	6
EAN/UPC - Case	50046677583588

Dimensional drawing



Product	D	C
8.8BR30/CNG/827/FR/P/E26/DIM/120V 6/1CT	3-3/4 inch	5-1/8 inch

Photometric data




General uniform lighting - 8.8BR30/CNG/827/FR/P/E26/DIM/120V 6/1CT

Spectral Power Distribution Colour - 8.8BR30/CNG/827/FR/P/E26/DIM/120V 6/1CT


LED BR30

Photometric data




Light Distribution Diagram - 8.8BR30/CNG/827/FR/P/E26/DIM/120V 6/1CT

Lifetime



Life Expectancy Diagram



Lumen Maintenance Diagram - 8.8BR30/CNG/827/FR/P/E26/DIM/120V 6/1CT

