Contractor-grade Plastic (Dimmable) A-Shape Lamps

8.8A19/CNG/827/FR/P/E26/D 12/1CT

Contractor grade, LED, A19, 60 W, E26, 2700 K, 800 lm, 15000 hour(s), Plastic

Plastic A19 offering dimmability and a lifetime over 15,000 hours. Ideal for contractor-grade residential and multi-family spaces.

Product data

General Information	
Cap-Base	E26
Nominal lifetime	15,000 hour(s)
Switching Cycle	50,000
Lighting Technology	LED

Light Technical	
Color Code	827 [CCT of 2700K]
Beam Angle (Nom)	180 degree(s)
Luminous Flux	800 lm
Color Designation	Warm White (WW)
Correlated Color Temperature (Nom)	2700 K
Luminous Efficacy (rated) (Nom)	90 lm/W
Color Consistency	<6
Color rendering index (CRI)	80
LLMF At End Of Nominal Lifetime (Nom)	70 %

Operating and Electrical	
Input Frequency	60 Hz
Power Consumption	8.8 W
Lamp Current (Nom)	95 mA
Wattage Equivalent	60 W
Starting Time (Nom)	0.5 s
Warm-up time to 60% light	0.5 s
Power Factor (Fraction)	0.7
Voltage (Nom)	120 V

Temperature	
T-Case Maximum (Nom)	90 °C

Contractor-grade Plastic (Dimmable) A-Shape Lamps

Controls and Dimming	
Dimmable	Only with specific dimmers

Mechanical and Housing	
Bulb Finish	Frosted
Bulb Material	Plastic
Bulb Shape	A19
UL Wet/ damp/ dry location	Damp location
Net Weight (Piece)	0.026 kg

Approval and Application	
EU RoHS compliant	Yes
T20 compliant	No
Ambient temperature range	-20 to +45 °C

Application Conditions	
can it be used in closed luminaires	No

Product Data	
Order product name	8.8A19/CNG/827/FR/P/E26/D 12/1CT
Full product name	8.8A19/CNG/827/FR/P/E26/D 12/1CT
Order code	929003579564
Material Nr. (12NC)	929003579564
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	046677589646
Numerator - Packs per outer box	12
EAN/UPC - Case	50046677589641

Dimensional drawing



Product	D	C
8.8A19/CNG/827/FR/P/E26/D 12/1CT	60 mm	104 mm

Photometric data



Spectral Power Distribution Colour - 8.8A19/CNG/827/FR/P/E26/D 12/1CT



General uniform lighting - 8.8A19/CNG/827/FR/P/E26/D 12/1CT

Contractor-grade Plastic (Dimmable) A-Shape Lamps

Photometric data



Light Distribution Diagram - 8.8A19/CNG/827/FR/P/E26/D 12/1CT

Lifetime



Life Expectancy Diagram



Lumen Maintenance Diagram - 8.8A19/CNG/827/FR/P/E26/D 12/1CT

© 2025 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.