HUBBELL
Premise Wiring

PROClick Connector, LC, OM3/OM4, Aqua, 12 Pack

By Hubbell Premise Wiring
Catalog # FCLC900K50GM12

Fiber Optic Connectors, ProClick LC, OM3/OM4, Pre-Polished, 10GHz 900, 12Pack

Features

- Terminate in Less than 60 Seconds
- RoHS Compliant and Bulk Packed in Recyclable Cartons

Application

Interconnect

Performance

Optical - Insertion loss - 0.5dB (0.35dB typical), 0.75dB max, Optical - Mating durability - 500 cycles <, 0.1dB change, Optical - Multimode return loss - 35dB Typ, 22dB minimum, Optical - Singlemode return loss - 55dB Typ, 40dB minimum, Environmental - Operating temperature - 0 ºC to +70 ºC

Specifications

Environmental Conditions	Indoor
Buy America(n) Qualified	TAA Compliant (All status valid till December 2026)
Industry Standard(s)	• Telcordia GR-326-CORE • TIA-568-C.3 • TIA-604-FOCIS

Conductor

Fiber Size	125 Micron
Fiber Type	OM3/OM4, MM

Configuration

Connector Type	LC

Current

Insertion Loss	0.75 dB Max
Return Loss	26
Connectivity	Fiber Optic Connector

Dimensions

Display Size	1.25 mm

General

Color	Aqua
Style	PROclick
Enclosure Type	Various
Sub Brand	OptiChannel
OEM Brand Name	Hubbell Premise Wiring
Specifications	• Cable Type - 900/250 µM • Ferrule Material - Zirconia ceramic, UPC polish • Fiber Type - 50µM, OM3
UPC	662620224121
Material - Mounting Hardware	Fiber Termination, No Polish
Item Type	LC
Material	Ceramic

Logistics

Pallet Quantity	1200
Carton Quantity	10

Operational

Repeatability	0.1 dB
Adapter Type	LC
Temperature Rating	0C to 70C
Service Life	500 matings

Product Assets

Catalog [English]
Catalog Page [English]
Catalog Page [English]
Catalog Page [English]
Catalog Page [English]
Catalog Page [English]
Customer Drawing [English]
Installation Manual [English]

© 2026 Hubbell Incorporated. All rights reserved