

HUBBELL

Premise Wiring

Fusion Splice Connector, LC, OS2, Blue, Blister Pack

By Hubbell Premise Wiring
Catalog # [FCLCF900SMBP](#)

Fiber Optic, Connector, Fusion Splice,LC, Singlemode, Pre-Polished, 900, Blister Pack

Features

- Pack of 10 connectors
- Each in a protective blister pack with cleave protector, 900µm boot and splice sleeve
- All Zirconia Ferrules
- Compatible with fusion splicers having a removable fiber holder
- Metal holder fixture required (sold separately)

Application

Interconnect

Performance

Optical - Insertion loss - 0.3dB (0.15dB typical), Optical - Mating durability - 500 cycles <, 0.1dB change, Optical return loss > 55dB Typical, Environmental - Operating temperature -40 °C to +70 °C, Cable Retention 2.5lbs

Specifications

- | | |
|----------------------|---|
| Industry Standard(s) | <ul style="list-style-type: none">• Telcordia GR-326-CORE• TIA-568-C.3• TIA-604-FOCIS |
|----------------------|---|

Conductor

Fiber Type	Singlemode
------------	------------



Configuration

Connector Type	LC
----------------	----

Current

Connectivity	Fiber Optic Connector
--------------	-----------------------

General

Color	Blue
Style	Fusion Splice-On
UPC	662620343471
Sub Brand	FIBERHUBB

Logistics

Pallet Quantity	1020
Carton Quantity	10

Operational

Adapter Type	LC
--------------	----

Product Assets

- [Catalog \[English\]](#)
- [Catalog Page \[English\]](#)
- [Catalog Page \[English\]](#)
- [Customer Drawing \[English\]](#)
- [Installation Manual \[English\]](#)