

PROclick Connector, SC, OM1, Beige, 100 Pack

By Hubbell Premise Wiring
Catalog # [FCSC900K62M12](#)



Fiber Optic Connectors, ProClick SC, OM1, Pre-Polished, 900, 12 Pack

Features

- Terminate in Less than 60 Seconds
- RoHS Compliant and Bulk Packed in Recyclable Cartons

Application

Interconnect

Performance

Optical - Insertion loss - 0.5dB (0.35dB typical), 0.75dB max, Optical - Mating durability - 500 cycles <, 0.1dB change, Optical - Multimode return loss - 35dB Typ, 22dB minimum, Optical - Singlemode return loss - 55dB Typ, 40dB minimum, Environmental - Operating temperature - 0 °C to +70 °C

Specifications

Environmental Conditions	Indoor
Industry Standard(s)	• Telcordia GR-326-CORE • TIA-568-C.3 • TIA-604-FOCIS

Conductor

Fiber Size	125 Micron
Fiber Type	OM1, MM

Configuration

Connector Type	SC
----------------	----

Current

Insertion Loss	0.75 dB Max
Return Loss	26
Connectivity	Fiber Optic Connector

Dimensions

Display Size	2.5 mm
--------------	--------

General

Color	Beige
Style	PROclick
Enclosure Type	Various
Sub Brand	OptiChannel
Specifications	• Cable Type - 900/250 μM • Ferrule Material - Zirconia ceramic, UPC polish • Fiber Type - 62.5μM, OM1 662620224091
UPC	Fiber Termination, No Polish
Material - Mounting Hardware	SC
Item Type	Ceramic
Material	

Logistics

Pallet Quantity	1680
Carton Quantity	10

Operational

Repeatability	0.1 dB
Adapter Type	SC
Temperature Rating	0C to 70C
Service Life	500 matings

Product Assets

[Catalog \[English\]](#)
[Catalog Page \[English\]](#)
[Catalog Page \[English\]](#)