HUBBELL
Premise Wiring

Fusion Splice Connector, SC, OM1, Beige, Blister Pack

By Hubbell Premise Wiring
Catalog # FCSCF900M62BP

Fiber Optic, Connector, Fusion Splice,Multimode, OM1, Pre-Polished, 900, Blister Pack

Features

- Pack of 10 connectors
- Each in a protective blister pack with cleave protector, 900µm boot and splice sleeve
- All Zirconia Ferrules
- Compatible with fusion splicers having a removable fiber holder
- Metal holder fixture required (sold separately)

Application

Interconnect

Performance

Optical - Insertion loss - 0.4dB (0.25dB typical), Optical - Mating durability - 500 cycles <, 0.1dB change, Optical return loss 35dB Typical, Environmental - Operating temperature -40 ºC to +85 ºC, Cable Retention 2.5lbs

Specifications

Industry Standard(s)	• Telcordia GR-326-CORE • TIA-568-C.3 • TIA-604-FOCIS

Conductor

Fiber Type	OM1, MM

Configuration

Connector Type	SC

Current

Connectivity	Fiber Optic Connector

General

Color	Beige
Style	Fusion Splice-On
UPC	662620343495
Sub Brand	FIBERHUBB

Logistics

Carton Quantity	10

Operational

Adapter Type	SC

Product Assets

Catalog [English]
Catalog Page [English]
Catalog Page [English]
Customer Drawing [English]
Installation Manual [English]

© 2026 Hubbell Incorporated. All rights reserved