

HUBBELL

Premise Wiring

ST 2Click, ST, OM1, Beige, 12 Pack

By Hubbell Premise Wiring
Catalog # [FCST62M12](#)

Fiber Optic Connectors, ST, Enhanced, OM1 Fiber, Pre-Polished, 12 Pack



Features

- Terminate in Less than 60 Seconds
- RoHS Compliant and Bulk Packed in Recyclable Cartons

Application

Interconnect

Performance

Optical - Insertion loss - 0.5dB (0.35dB typical), 0.75dB max, Optical - Mating durability - 500 cycles <, 0.1dB change, Optical - Multimode return loss - 35dB Typ, 22dB minimum, Optical - Singlemode return loss - 55dB Typ, 40dB minimum, Environmental - Operating temperature - 0 °C to +70 °C

Specifications

Environmental Conditions	Indoor
Industry Standard(s)	• Telcordia GR-326-CORE • TIA-568-C.3 • TIA-604-FOCIS

Conductor

Fiber Size	125 Micron
Fiber Type	OM1, MM

Configuration

Connector Type	SC
----------------	----

Current

Insertion Loss	0.75 dB Max
Return Loss	26
Connectivity	Fiber Optic Connector

Dimensions

Display Size	2.5 mm
--------------	--------

General

Color	Beige
Style	ST 2Click
Enclosure Type	Various
Sub Brand	OptiChannel
Specifications	• Cable Type - 900/250 μM • Ferrule Material - Zirconia ceramic, UPC polish • Fiber Type - 62.5μM, OM1 662620217475
UPC	Fiber Termination, No Polish
Material - Mounting Hardware	ST
Item Type	Ceramic
Material	

Logistics

Carton Quantity	25
-----------------	----

Operational

Repeatability	0.1 dB
Adapter Type	SC
Temperature Rating	0C to 70C
Service Life	500 matings

Product Assets

- [Catalog \[English\]](#)
[Catalog Page \[English\]](#)
[Catalog Page \[English\]](#)