

Fiber Optic Panel Adapter, 8 Fiber, 8 FC
Simplex, Zircon Sleeves

By Hubbell Premise Wiring
Catalog # [FSPNFCSS8](#)

Fiber Optic Panel Adapter, 8 Fiber, 8) FC Simplex, Zircon Sleeves



Features

- Wide Range of Adapter Types
- Quick and Easy Snap-in Design
- Premium Quality and High Performance

Application

Interconnect

Performance

Optical - SM/MM insertion loss - Less than 0.50dB (0.25dB typical),
Environmental - Operating temperature - 0 °C to +75 °C

Conductor

Fiber Size	125 Micron
Fiber Type	Singlemode or Multimode

Configuration

Number Of Ports	8
-----------------	---

Current

Return Loss	55
-------------	----

General

Color	Black
UPC	662620671673
Sub Brand	OptiChannel

Logistics

Carton Quantity	4
-----------------	---

Operational

Repeatability	0.1 dB SM / 0.2 dB MM
Service Life	500 matings
Single/Multimode	SM/MM
Adapter Type	FC Simplex
Temperature Rating	-40C to +85C

Product Assets

- [Catalog \[English\]](#)
- [Catalog Page \[English\]](#)
- [Catalog Page \[English\]](#)