HUBBELL
Premise Wiring

Fiber Optic Panel Adapter, 6-Fiber, 3LC Duplex, Zircon Sleeves, Beige

By Hubbell Premise Wiring
Catalog # FSPNLCDS3BE

Fiber Optic Panel Adapter, 6-Fiber, 3)LC Duplex, Zircon Sleeves, Beige

Features

- Premium Quality and High Performance Design

Application

Interconnect

Performance

Optical - SM/MM insertion loss - Less than 0.50dB (0.25dB typical),
Environmental - Operating temperature - 0 ºC to +75 ºC

Specifications

Industry Standard(s)	• TIA-568-C.3 • TIA-604-FOCIS

Conductor

Fiber Size	125 Micron
Fiber Type	Singlemode or Multimode

Configuration

Number Of Ports	6

Current

Insertion Loss	0.30 dB

Dimensions

Size	5.1" X 1.1"

General

Color	Beige
UPC	662620671819
Material - Mounting Hardware	Snap-In
Sub Brand	OptiChannel
Material	Ceramic Zirconium

Logistics

Carton Quantity	4

Operational

Repeatability	0.1 dB SM / 0.2 dB MM
Service Life	500 matings
Single/Multimode	SM/MM
Adapter Type	LC Duplex
Temperature Rating	-40C to +85C

Product Assets

Catalog [English]
Catalog Page [English]
Catalog Page [English]

© 2026 Hubbell Incorporated. All rights reserved