

HUBBELL  
Premise Wiring

Fiber Optic Panel Adapter, 24-Fiber, 6 LC  
Quads, Zircon Sleeves, EVI

By Hubbell Premise Wiring  
Catalog # [FSPNLCQS6VI](#)

Fiber Adapter Panel, 24-Fiber, 6) LC Quads, Zircon Sleeves, EVI



Features

- Premium Quality and High Performance Design

Application

Interconnect

Specifications

- |                      |                                                                                   |
|----------------------|-----------------------------------------------------------------------------------|
| Industry Standard(s) | <ul style="list-style-type: none"><li>TIA-568-C.3</li><li>TIA-604-FOCIS</li></ul> |
|----------------------|-----------------------------------------------------------------------------------|

Conductor

- |            |                         |
|------------|-------------------------|
| Fiber Size | 125 Micron              |
| Fiber Type | Singlemode or Multimode |

Configuration

- |                 |    |
|-----------------|----|
| Number Of Ports | 24 |
|-----------------|----|

Current

- |                |         |
|----------------|---------|
| Insertion Loss | 0.30 dB |
|----------------|---------|

Dimensions

- |      |             |
|------|-------------|
| Size | 5.1" X 1.1" |
|------|-------------|

General

- |                              |                   |
|------------------------------|-------------------|
| Color                        | Violet            |
| UPC                          | 662620340128      |
| Material - Mounting Hardware | Snap-In           |
| Sub Brand                    | OptiChannel       |
| Material                     | Ceramic Zirconium |

Logistics

- |                 |   |
|-----------------|---|
| Carton Quantity | 4 |
|-----------------|---|

Operational

- |                    |                       |
|--------------------|-----------------------|
| Repeatability      | 0.1 dB SM / 0.2 dB MM |
| Service Life       | 500 matings           |
| Single/Multimode   | SM/MM                 |
| Adapter Type       | LC Quad               |
| Temperature Rating | -40C to +85C          |

Product Assets

- [Catalog \[English\]](#)  
[Catalog Page \[English\]](#)  
[Catalog Page \[English\]](#)