

Fiber Optic Panel Adapter, 6-Fiber, SC/APC Simplex, 6-Port, Loaded with 6 Adapters, Zircon Sleeves, Green

By Hubbell Premise Wiring
Catalog # [FSPNSCA6](#)

FSP Adapter Panel, 6-Fiber, SC/APC Simplex, 6-Port, Loaded with 6 Adapters, Zircon Sleeves, Green



Features

- Wide Range of Adapter Types
- Quick and Easy Snap-in Design
- Premium Quality and High Performance

Application

Interconnect

Performance

Optical - SM/MM insertion loss - Less than 0.50dB (0.25dB typical),
Environmental - Operating temperature - 0 °C to +75 °C

Specifications

- | | |
|----------------------|---|
| Industry Standard(s) | <ul style="list-style-type: none">• TIA-568-C.3• TIA-604-FOCIS |
|----------------------|---|

Conductor

- | | |
|------------|-------------------------|
| Fiber Size | 125 Micron |
| Fiber Type | Singlemode or Multimode |

Configuration

- | | |
|-----------------|---|
| Number Of Ports | 6 |
|-----------------|---|

Current

- | | |
|----------------|---------|
| Insertion Loss | 0.30 dB |
| Return Loss | 55 |

General

- | | |
|------------------------------|-------------------|
| Color | Green |
| UPC | 662620340203 |
| Material - Mounting Hardware | Snap-In |
| Sub Brand | OptiChannel |
| Material | Ceramic Zirconium |

Logistics

- | | |
|-----------------|---|
| Carton Quantity | 4 |
|-----------------|---|

Operational

- | | |
|--------------------|-----------------|
| Repeatability | 0.1 dB |
| Service Life | 500 matings |
| Single/Multimode | SM |
| Adapter Type | SC Simplex, APC |
| Temperature Rating | -40C to +85C |

Product Assets

- [Catalog \[English\]](#)
[Catalog Page \[English\]](#)
[Catalog Page \[English\]](#)