

Copper Solutions, Patch Cords, Ascent,
Cat6A, Slim, 3' Length, Blue

By Hubbell Premise Wiring
Catalog # [HC6AB03](#)

Copper Solutions, Patch Cords, Ascent, Cat6A, Slim, 3' Length,
Blue



Features

- Third Party Verified Category 6A Component
- Plug Optimized For High Density Switch Ports
- 10-Gigabit Application Assurance
- Qualified to 150% of 802.3bt PoE Current Level

Performance

Mechanical - Cable to plug tensile strength - 20+ lbs., Mechanical
- Mating Cycles - 2000+

Specifications

EU RoHS Indicator	Yes
Industry Standard(s)	• ANSI/TIA/EIA-568-C.2 Category 6A Component • ISO 11801/60603-7-41 Category 6A Component

Conductor

Number Of Conductors	8-Conductor
Wire Size	#24 AWG
Conductor Type	Copper
Conductor Stranding	Stranded

Configuration

Boot Type	PVC
-----------	-----

Current

Voltage Rating	300V AC kV
----------------	------------

Dimensions

Length	3 ft
Outside Diameter	0.218

General

Color	Blue
Plug Type	RJ45
Specifications	• Conductor - 26AWG UTP • Contact Plating - 50 micro-inch Gold with 100 micro-inch under plating • Jacket - Dual Layer Flame-Retardant PVC - CM Rated • Plug Body - Polycarbonate UL 94V-0 • Plug Boot - Polycarbonate UL 94V-0
UPC	662620228969
Type	Standard
Item Type	NEXTSPEED Ascent Category 6A Patch Cords
Material - Jacket	Flame Redardant PVC
Material - Insulation	Flame Redardant PVC

Logistics

Pallet Quantity	2400
Carton Quantity	40

Operational

Temperature Rating	Per TIA
Attenuation	.1dB

Product Assets

- [Catalog \[English\]](#)
- [Catalog Page \[English\]](#)
- [Catalog Page \[English\]](#)