HUBBELL
Premise Wiring

# Copper Solutions, Patch Cords, Ascent, Cat6A, Slim, 15′ Length, Red



By Hubbell Premise Wiring
Catalog # HC6AR15

Copper Solutions, Patch Cords, Ascent, Cat6A, Slim, 15′ Length, Red

## Features

- Third Party Verified Category 6A Component
- Plug Optimized For High Density Switch Ports
- 10-Gigabit Application Assurance
- Qualified to 150% of 802.3bt PoE Current Level

## Specifications

| | |
|---|---|
| Industry Standard(s) | • ANSI/TIA/EIA-568-C.2 Category 6A Component<br>• ISO 11801/60603-7-41 Category 6A Component |
| EU RoHS Indicator | Yes |

## Conductor

| | |
|---|---|
| Conductor Type | Copper |
| Conductor Stranding | Stranded |
| Number Of Conductors | 8-Conductor |
| Wire Size | #24 AWG |

## Current

| | |
|---|---|
| Voltage Rating | 300V AC kV |

## Dimensions

| | |
|---|---|
| Length | 15 ft |
| Outside Diameter | 0.218 |

## General

| | |
|---|---|
| Specifications | • Conductor - 26AWG UTP<br>• Contact Plating - 50 micro-inch Gold with 100 micro-inch under plating<br>• Jacket - Dual Layer Flame-Retardant PVC - CM Rated<br>• Plug Body - Polycarbonate UL 94V-0<br>• Plug Boot - Polycarbonate UL 94V-0 |
| Color | Red |
| UPC | 662620230849 |
| Type | Standard |
| Plug Type | RJ45 |
| Material - Jacket | Flame Redardant PVC |
| Material - Insulation | Flame Redardant PVC |

## Operational

| | |
|---|---|
| Temperature Rating | Per TIA |

## Product Assets

Catalog [English]
Catalog Page [English]
Catalog Page [English]



© 2026 Hubbell Incorporated. All rights reserved