

HUBBELL

Premise Wiring

HFCD1 Series Indoor Tight Buffer Distribution, 2 strand, Plenum, OM4, MM, Aqua Jacket

By Hubbell Premise Wiring
Catalog # [HFCD1002P4](#)

HFCD1 Series Indoor Tight Buffer Distribution, 2 strand, Plenum, OM4, MM , Aqua Jacket

Features

- Multimode Bend-Insensitive Optical Fiber
- E-Z Strip Buffer For Contractor-Friendly Termination
- Compact Cable Diameter Reduces Pathway Congestion
- Premium Fiber For Enhanced Optical Performance

Application

Data Transmission

Specifications

Industry Standard(s) TIA

Conductor

Number Of Fibers 2
Fiber Size OM4
Fiber Type OM4, MM

Current

Wavelength 850/1300 Nanometers

General

Specifications

- Armor - None



- Cable Diameter in (mm) - 0.17 (4.4)
- Cable Weight (lb/kft) - 12
- Construction - Single Unit, Aramid Strength Member
- Fiber Coating - 900 Micron PVC Tight Buffer

Color Aqua
UPC 662620555461
Type Cable
Sub Brand Fiber Optics
Material - Jacket PVC
Cable Rating Plenum

Operational

Bandwidth 4000 bps
Attenuation 3.5/1.5 Db per Kilometer
Temperature Rating 0 Degrees C to 70 Degrees C

Product Assets

[Catalog \[English\]](#)
[Catalog Page \[English\]](#)
[Catalog Page \[English\]](#)