HUBBELL
Premise Wiring

HFCD1 Series Indoor Tight Buffer Distribution, 12 strand, Riser, OM4, MM, Aqua Jacket

By Hubbell Premise Wiring
Catalog # HFCD1012R4

HFCD1 Series Indoor Tight Buffer Distribution, 12 strand, Riser, OM4, MM , Aqua Jacket

Features

- Multimode Bend-Insensitive Optical Fiber
- E-Z Strip Buffer For Contractor-Friendly Termination
- Compact Cable Diameter Reduces Pathway Congestion
- Premium Fiber For Enhanced Optical Performance

Application

Data Tranmission

Specifications

Industry Standard(s)	• ANSI/ICEA S-83-596 • NFPA-262/UL910/CSA FT-4 • Telcordia GR-409 • TIA-568.3-D

Conductor

Number Of Fibers	12
Fiber Size	OM4
Fiber Type	OM4, MM

Current

Wavelength	850/1300 Nanometers

General

Specifications	• Armor - None • Cable Diameter in (mm) - 0.25 (6.3) • Cable Weight (lb/kft) - 35 • Construction - Single Unit, Aramid Strength Member • Fiber Coating - 900 Micron PVC Tight Buffer
Color	Aqua
UPC	662620333632
Type	Cable
Sub Brand	Fiber Optics
Material - Jacket	PVC
Cable Rating	Riser

Operational

Bandwidth	4000 bps
Attenuation	3.5/1.5 Db per Kilometer
Temperature Rating	-20 Degrees C to 70 Degrees C

Product Assets

Catalog [English]
Catalog Page [English]
Catalog Page [English]

© 2026 Hubbell Incorporated. All rights reserved