

HFCD15 Series Indoor Tight Buffer
Distribution, 12 strand, Plenum, Armored,
OM3, MM, Aqua Jacket

By Hubbell Premise Wiring
Catalog # [HFCD15012P3](#)

HFCD15 Series Indoor Tight Buffer Distribution, 12 strand, Plenum,
Armored, OM3, MM , Aqua Jacket

Features

- Multimode Bend-Insensitive Optical Fiber
- E-Z Strip Buffer For Contractor-Friendly Termination
- Durable Aluminum Interlock Armor
- Premium Fiber For Enhanced Optical Performance

Application

Data Transmission

Specifications

Industry Standard(s)	• ANSI/ICEA S-83-596 • NFPA-262/UL910/CSA FT-6 • Telcordia GR-409 • TIA-568.3-D
----------------------	---

Conductor

Number Of Fibers	12
Fiber Size	OM3
Fiber Type	OM3, MM

Current

Wavelength	850/1300 Nanometers
------------	---------------------

General

Specifications

Color
UPC
Type
Sub Brand
Material - Jacket
Cable Rating

Operational

Bandwidth
Attenuation
Temperature Rating

Product Assets

- [Catalog \[English\]](#)
- [Catalog Page \[English\]](#)
- [Catalog Page \[English\]](#)



- Armor - Aluminum Interlock
- Cable Diameter in (mm) - 0.63 (16)
- Cable Weight (lb/kft) - 170
- Construction - Single Unit, Aramid Strength Member
- Fiber Coating - 900 Micron PVC Tight Buffer

Aqua
662620326566
Cable
Fiber Optics
PVC
Plenum, Armored

2000 bps
3.5/1.5 Db per Kilometer
0 Degrees C to 70 Degrees C