

# HUBBELL

## Premise Wiring

### HFCD19 Series Indoor/Outdoor Tight Buffer, 6 strand, Plenum, Armored, OM3, MM, Black Jacket

By Hubbell Premise Wiring  
Catalog # [HFCD19006P3BK](#)

HFCD19 Series Indoor/Outdoor Tight Buffer, 6 strand, Plenum, Armored, OM3, MM , Black Jacket

#### Features

- Multimode Bend-Insensitive Optical Fiber
- E-Z Strip Buffer For Contractor-Friendly Termination
- Multi-Purpose Outdoor Duct To Building Riser Application
- Premium Fiber For Enhanced Optical Performance

#### Application

Data Transmission

#### Specifications

|                      |                                                                                                                                                         |
|----------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------|
| Industry Standard(s) | <ul style="list-style-type: none"><li>• ANSI/ICEA S-83-596</li><li>• NFPA-262/UL910/CSA FT-6</li><li>• Telcordia GR-409</li><li>• TIA-568.3-D</li></ul> |
|----------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------|

#### Conductor

|                  |         |
|------------------|---------|
| Number Of Fibers | 6       |
| Fiber Size       | OM3     |
| Fiber Type       | OM3, MM |

#### Current

|            |                     |
|------------|---------------------|
| Wavelength | 850/1300 Nanometers |
|------------|---------------------|

#### General

#### Specifications

|                   |                 |
|-------------------|-----------------|
| Color             | Black           |
| UPC               | 662620332284    |
| Type              | Cable           |
| Sub Brand         | Fiber Optics    |
| Material - Jacket | PVC             |
| Cable Rating      | Plenum, Armored |

#### Operational

|                    |                             |
|--------------------|-----------------------------|
| Bandwidth          | 2000 bps                    |
| Attenuation        | 3.5/1.5 Db per Kilometer    |
| Temperature Rating | 0 Degrees C to 70 Degrees C |

#### Product Assets

- [Catalog \[English\]](#)
- [Catalog Page \[English\]](#)
- [Catalog Page \[English\]](#)



- Armor - Aluminum Interlock
- Cable Diameter in (mm) - 0.63 (16)
- Cable Weight (lb/kft) - 165
- Construction - Single Unit, Aramid Strength Member
- Fiber Coating - 900 Micron PVC Tight Buffer