HUBBELL
Premise Wiring

HFCD19 Series Indoor/Outdoor Tight Buffer, 6 strand, Plenum, Armored, OM4, MM, Black Jacket

By Hubbell Premise Wiring
Catalog # HFCD19006P4BK

HFCD19 Series Indoor/Outdoor Tight Buffer, 6 strand, Plenum, Armored, OM4, MM , Black Jacket

Features

- Multimode Bend-Insensitive Optical Fiber
- E-Z Strip Buffer For Contractor-Friendly Termination
- Multi-Purpose Outdoor Duct To Building Riser Application
- Premium Fiber For Enhanced Optical Performance

Application

Data Tranmission

Specifications

Industry Standard(s)	• ANSI/ICEA S-83-596 • NFPA-262/UL910/CSA FT-6 • Telcordia GR-409 • TIA-568.3-D

Conductor

Number Of Fibers	6
Fiber Size	OM4
Fiber Type	OM4, MM

Current

Wavelength	850/1300 Nanometers

General

Specifications	• Armor - Aluminum Interlock • Cable Diameter in (mm) - 0.63 (16) • Cable Weight (lb/kft) - 165 • Construction - Single Unit, Aramid Strength Member • Fiber Coating - 900 Micron PVC Tight Buffer
Color	Black
UPC	662620332291
Type	Cable
Sub Brand	Fiber Optics
Material - Jacket	PVC
Cable Rating	Plenum, Armored

Operational

Bandwidth	4000 bps
Attenuation	3.5/1.5 Db per Kilometer
Temperature Rating	0 Degrees C to 70 Degrees C

Product Assets

Catalog [English]
Catalog Page [English]
Catalog Page [English]

© 2026 Hubbell Incorporated. All rights reserved