

Fiber LGX Cassette, OM4, LC Duplex to MTP, Aqua

By Hubbell Premise Wiring  
Catalog # [OCLCD40G8](#)

Fiber Optic, Cassette Adapter Panel, 40 Gig, LC to MTP, OM4, 8 Fiber, Aqua



Features

- Compact Universal Design
- Ten Gigabit Ethernet Assurance
- Quick and Easy Plug-n-Play Installation

Application

Interconnect

Performance

Optical - Total insertion loss - Less than 1.5dB (test data included)

Specifications

|                          |                                                                                                                       |
|--------------------------|-----------------------------------------------------------------------------------------------------------------------|
| Industry Standard(s)     | <ul style="list-style-type: none"><li>• Telcordia GR-326-CORE</li><li>• TIA-568-C.3</li><li>• TIA-604-FOCIS</li></ul> |
| Environmental Conditions | Indoor                                                                                                                |

Conductor

|            |            |
|------------|------------|
| Fiber Size | 250 Micron |
| Fiber Type | OM4        |

Current

|                |             |
|----------------|-------------|
| Insertion Loss | 0.75 dB Max |
| Return Loss    | 55          |
| Connectivity   | Cassette    |

Dimensions

|              |             |
|--------------|-------------|
| Display Size | 5.1" X 1.1" |
|--------------|-------------|

General

|                              |                  |
|------------------------------|------------------|
| Color                        | Aqua             |
| Style                        | LC-MTP           |
| UPC                          | 662620606545     |
| Material - Mounting Hardware | Snap-In          |
| Item Type                    | LC Duplex to MTP |
| Sub Brand                    | OptiChannel      |
| Material                     | Ceramic          |

Logistics

|                 |    |
|-----------------|----|
| Carton Quantity | 25 |
|-----------------|----|

Operational

|                    |             |
|--------------------|-------------|
| Repeatability      | 0.1 dB      |
| Service Life       | 500 matings |
| Temperature Rating | 0C to 70C   |

Product Assets

[Catalog \[English\]](#)  
[Catalog Page \[English\]](#)  
[Catalog Page \[English\]](#)