HUBBELL
Premise Wiring

Fiber LGX Cassette, OS2, LC Quad to MTP, Blue

By Hubbell Premise Wiring
Catalog # OCLCSM

Fiber Accessory, Plug and Play Cassette, LC, Single Mode

Features

- Compact Universal Design
- Ten Gigabit Ethernet Assurance
- Quick and Easy Plug-n-Play Installation

Application

Interconnect

Performance

Optical - Return loss - More than 50dB, Optical - Total insertion loss - Less than 1.1dB (test data included)

Specifications

Environmental Conditions	Indoor
Industry Standard(s)	• Telcordia GR-326-CORE • TIA-568-C.3 • TIA-604-FOCIS

Conductor

Fiber Size	250 Micron
Fiber Type	OS2

Current

Insertion Loss	0.75 dB Max
Return Loss	55
Connectivity	Cassette

Dimensions

Display Size	5.1" X 1.1"

General

Color	Blue
Style	LC Duplex 12F
Sub Brand	OptiChannel
OEM Brand Name	Hubbell Premise Wiring
Specifications	• Cassette Type - LC Duplex 12F • Dimensions - 5.1" H x 1.1" W x 2.75" D • Fiber Type - SM, OS2 • Housing material - 16ga powder coated steel • MTP connector - 12-fiber male receptacle on back side • Sleeve material - Ceramic
UPC	662620844800
Material - Mounting Hardware	Snap-In
Item Type	LC Duplex to MTP
Material	Ceramic

Logistics

Carton Quantity	25

Operational

Repeatability	0.1 dB
Temperature Rating	0C to 70C
Service Life	500 matings

Product Assets

Catalog [English]
Catalog Page [English]
Catalog Page [English]

© 2026 Hubbell Incorporated. All rights reserved