



Color: Satin silver

Weight: 0.4 lbs

Project:

Type:

Prepared By:

Date:

Driver Info		LED Info	
Type	Constant Current	Watts	12W
120V	0.11A	Color Temp	3000K
208V	N/A	Color Accuracy	90 CRI
240V	N/A	L70 Lifespan	50,000 Hours
277V	N/A	Lumens	845 lm
Input Watts	12W	Efficacy	0

Technical Specifications

Performance

Description:
The DISK34 is an ultra low profile surface-mount, ideal solution for new construction and retrofit applications. IC rated for direct contact with insulation, air tight, suitable for indoor applications in dry and damp environments. Mounting kit for recessed housing sold separately.

Product Type:
Surface & Flush Mounts

Input Wattage:
12W

Lumens:
750lm

Efficacy:
62.5lm/W

L70 Lifespan:
50,000-Hour LED lifespan based on IES LM-70 results

Compliance

UL Listed:
Suitable for damp locations

UL Classified:
Yes

Fixture Rating:
Open

IC Rated:
Suitable for direct contact with insulation

Electrical

Dimming Driver:
TRIAC compatible dimmer with dimming as low as 5%

Power Factor:
0.9

Flicker:
<30%

Input Voltage:
120V

Operating Frequency:
60Hz

Construction

Material:
Aluminum

Trim Style:
Smooth Trim

Shape:
Round

Operating Temperature:
-22°F (-30°C) to 104°F (40°C)

LED Characteristics

Beam Angle:
110°

R9 Value:
High color performance with R9 greater than 50


Installation

Mounting:
Surface mount

Other

5-Year, No-Compromise Warranty:
RAB warrants that our LED products will be free from defects in materials and workmanship for a period of five (5) years from the date of delivery to the end user, including coverage of light output, color stability, driver performance and fixture finish. RAB's warranty is subject to all terms and conditions found at rablighting.com/warranty.

Dimensions



Features

- Super low profile backlit LED with driverless design
- Stamped aluminum housing
- New construction or retrofit applications
- Simple and quick installation from below the ceiling
- Installs on standard 4" and 6" junction boxes
- Can be retrofitted to existing downlight housings with option accessory
- Suitable for Damp locations
- Dimmable down to 5% on compatible dimmers
- 5-Year, limited warranty

Ordering Matrix

Family		Size	Shape	Wattage	CRI/Color Temp	Driver	Finish	Trim
DSK34	-	4	R	12	930	120	BN	S
		6 = 6" 4 = 4"	R = Round	12 = 12W 14 = 14W 16 = 16W 16.5 = 16.5W	935 = 90 CRI, 3500K 927 = 90 CRI, 2700K 930 = 90 CRI, 3000K 940 = 90 CRI, 4000K 950 = 90 CRI, 5000K	120 = 120V	W = White B = Black BR = Bronze BN = Brushed Nickel	S = Smooth