T5HO-22-48P-840-EXT

RAB

Project:	Type:	Prepared By:	Date:

UPC: 192552005814

Features and Benefits

Replacement for conventional fluorescent T8 and T12 linear tubes

Technical Specifications

Performance

Product Type:
Linear

Input Wattage:
22W

Lumens:
3,400lm

Efficacy:
131lm/W

L70 Lifespan:
50,000-Hour LED lifespan based on IES LM-70 results

Compliance

UL Listed:
Suitable for damp locations

Enclosed Fixtures:
Suitable for use in enclosed fixtures

LED Characteristics

Color Temperature:
4000K

Color Accuracy (CRI):
≥80 CRI

Beam Angle:
145°

Construction

Shape:
T5 4 ft

Endcap Material:
Plastic

Enclosure Material:
Polycarbonate and Aluminum

Installation

Base Type:
G5

Electrical

THD:
20%

Power Factor:
0.9

Operating Temperature:
-20°C to 45°C (-4°F to 113°F)

Input Voltage:
Driver Dependent

Operating Frequency:
50/60Hz

Dimming:
Yes with 0-10V dimmer. See Dimmer Compatibility List.

Other

5-Year, No-Compromise Warranty:
RAB warrants that our LED products will be free from defects in materials and workmanship for a period of five (5) years from the date of delivery to the end user, including coverage of light output, color stability, driver performance and fixture finish. RAB's warranty is subject to all terms and conditions found at rablighting.com/warranty.

Copyright © 2026 RAB Lighting All Rights Reserved Note: Specifications are subject to change at any time without notice

Minimum Compartment Size

Length x Width x Height [in]	Lamp Quantity
20	1

Case and Pallet Dimensions

	QTY	LENGTH (in)	WIDTH (in)	HEIGHT (in)
CASE	24	6.7	5.1	7
PALLET	48	48.82	40.16	40.94

Dimension



Copyright © 2026 RAB Lighting All Rights Reserved Note: Specifications are subject to change at any time without notice