



Color: Bronze

Weight: 32.9 lbs

Project:

Type:

Prepared By:

Date:

Driver Info

Type	Constant
120V	4.23A
208V	2.45A
240V	2.12A
277V	1.87A
Input Watts	373.7-496.2W

LED Info

Watts	500/450/420/380W
Color Temp	N/A
Color Accuracy	N/A
L70 Lifespan	N/A
Lumens	53,877-74,093 lm
Efficacy	132.3-157.8 lm/W

Technical Specifications

Field Adjustability

Optical Field Adjustability:
90°, 75° and 55°

Field Adjustable:

Field Adjustable Light Output:
500W/460W/420W/380W (factory default 500W)
Color Temperature Selectable:
3000K, 4000K and 5000K (factory default 4000K)

Compliance

UL Listed:

Suitable for wet locations

IESNA LM-79 & LM-80 Testing:

RAB LED luminaires and LED components have been tested by an independent laboratory in accordance with IESNA LM-79 and LM-80.

IP Rating:

Ingress protection rating of IP65 for dust and water

DLC Listed:

This product is listed by Design Lights Consortium (DLC) as an ultra-efficient premium product that qualifies for the highest tier of rebates from DLC Member Utilities. Designed to meet DLC 5.1 requirements.
DLC Product Code: S-RPXWQ1

Electrical

Driver:

500W: Constant Current, Class 1, 120-277V, 50/60Hz, 120V: 4.23A, 208V: 2.45A, 240V: 2.12A, 277V: 1.87A

450W: Constant Current, Class 1, 120-277V, 50/60Hz, 120V: 3.85A, 208V: 2.18A, 240V: 1.90A, 277V: 1.67A

420W: Constant Current, Class 1, 120-277V, 50/60Hz, 120V: 3.43A, 208V: 2.02A, 240V: 1.74A, 277V: 1.54A

380W: Constant Current, Class 1, 120-277V, 50/60Hz, 120V: 3.11A, 208V: 1.83A, 240V: 1.59A, 277V: 1.41A

Dimming Driver:

Driver includes dimming control wiring for 0-10V dimming systems. Requires separate 0-10V DC dimming circuit. Dims down to 10%.

THD:

2.86% at 120V, 4.99% at 277V

Power Factor:

99.9% at 120V, 97.2% at 277V

Surge Protection:

L/N-PE: 2.5kV, L-N: 2.5kV

Photocell:

Integrated photocell included with on/off switch

LED Characteristics

LEDs:

Long-life, high-efficacy, surface-mount LEDs

Color Uniformity:

RAB's range of Correlated Color Temperature follows the guidelines of the American National Standard for Specifications for the Chromaticity of Solid State Lighting (SSL) Products, ANSI C78.377-2017.

Color Consistency:

3000K & 5000K: 5-step MacAdam Ellipse binning to achieve consistent fixture-to-fixture color
4000K: 7-step MacAdam Ellipse binning to achieve consistent fixture-to-fixture color

Performance

Lifespan:

100,000-Hour LED lifespan based on IES LM-80 results and TM-21 calculations

Performance Data:

[Click here for the X22-500 performance data](#)

Technical Specifications (continued)

Wattage Equivalency:

500W: Replaces up to 2000W Metal Halide (MH) or 1500W High Pressure Sodium (HPS)

450W: Replaces up to 2000W Metal Halide (MH) or 1500W High Pressure Sodium (HPS)

420W: Replaces up to 2000W Metal Halide (MH) or 1500W High Pressure Sodium (HPS)

380W: Replaces up to 1500W Metal Halide (MH) or 1000W High Pressure Sodium

Construction

Cold Weather Starting:

The minimum starting temperature is -30°C (-22°F)

Maximum Ambient Temperature:

Suitable for use in up to 50°C (122°F)

Housing:

Die-cast aluminum

Mounting:

Robust knuckle mount with 180° adjustable swivel arm. Tilt angle in 10° increments. Yoke kit is included.

Lens:

Tempered glass

Effective Projected Area:

1 Fixture: 1.142 ft²

2 Fixtures at 90°: 2.712 ft²

2 Fixtures at 180°: 2.285 ft²

3 Fixtures at 90°: 3.854 ft²

4 Fixtures at 90°: 3.854 ft²

Finish:

Formulated for high durability and long-lasting color

Green Technology:

Mercury and UV free. RoHS-compliant components.

Other

Note:

All values are typical (tolerance +/- 10%)


5 Yr Limited Warranty:

The RAB 5-year, limited warranty covers light output, driver performance and paint finish. RAB's warranty is subject to all terms and conditions found at rablighting.com/warranty.

Buy American Act Compliance:

RAB values USA manufacturing! Upon request, RAB may be able to manufacture this product to be compliant with the Buy American Act (BAA). Please contact customer service to request a quote for the product to be made BAA compliant.

Dimensions



Features

- DLC Premium listed
- IP65 Rated
- 100,000-Hour LED lifespan
- 5-Year, limited warranty

Ordering Matrix

Family		Wattage	Color Temp	Mounting	Finish	Beam Angle	Voltage	Options
X22	–	500		Blank				
		35 = 35/30/25/20W 60 = 60/50/40/30W 80 = 80/70/60/50W 150 = 150/125/100/75W 250 = 250/220/190/160W 320 = 320/280/240/200W 420 = 420/380/340/300W 500 = 500/450/420/380W 20 = 20/17/13/10W	Blank = 3000K/4000K/5000K CCT Adjustable	Blank = Knuckle Mount Installed with Yoke Kit Included Blank = Knuckle Mount Installed with Trunnion Kit Included Blank = Slipfitter Mount Installed with Trunnion Kit Included	Blank = Bronze W = White	Blank = Selectable Beam Angle (Medium to Very Wide Flood 55-100°)	Blank = 120-277V /480 = 480V, 0-10V Dimming	Blank = Selectable On/Off Photocell

X22-20 & X22-35: Knuckle mount installed with yoke mount included.
X22-60 & X22-80: Knuckle mount installed with trunnion mount included.
X22-150-500: Slipfitter mount installed with trunnion mount included. 480V only available in 150W-500W.