



2-1/2 in. Flex Squeeze Connector, Insulated

By RACO
Catalog # 3210

2-1/2 in. Flex Squeeze Connector, Insulated



Features

- All malleable construction ensures mechanical protection for the raceway
- Electro zinc plated for added corrosion protection
- UPC bar coded fittings are individually polybagged with a preprinted UPC-A bar code and packaged in pre-scored tear top cartons for an attractive presentation
- Additional sizes available

Specifications

Buy American Compliant	Contact Manufacturer
Certified Listed	cULus Listed
Buy America(n) Qualified	Contact Manufacturer

Configuration

Connector Type	Squeeze
----------------	---------

Dimensions

Length	7.563 in
Trade Size	2-1/2 in
Weight	3.652 lb.
Height	5.25 in

Width	4.328 in
Dimensions	7.563 in x 4.328 in x 5.25 in

General

Conduit Type	Flexible Metal Conduit
Product Family	Flexible Metal
Insulation Type	Insulated
Fitting Type	Connectors
Product Type	Commercial Fittings
UPC	050169032107
Material	Malleable Iron

Logistics

Minimum Pack Quantity	1
Pallet Quantity	360
Carton Quantity	1

Product Assets

- [Catalog \[English\]](#)
- [Catalog \[English\]](#)
- [Catalog Page \[English\]](#)
- [Catalog Page \[English\]](#)