



2-1/2 in. Flex Straight Squeeze Connector, Insulated

By RACO
Catalog # 3310

2-1/2 in. Flex Straight Squeeze Connector, Insulated



Features

- All malleable construction ensures mechanical protection for the raceway
- Electro zinc plated for added corrosion protection
- UPC bar coded fittings are individually polybagged with a preprinted UPC-A bar code and packaged in pre-scored tear top cartons for an attractive presentation
- Additional sizes available

Specifications

Buy American Compliant	Contact Manufacturer
Certified Listed	cULus Listed
Buy America(n) Qualified	Contact Manufacturer

Configuration

Connector Type	Squeeze
----------------	---------

Dimensions

Length	3 in
Trade Size	2-1/2 in
Weight	1.736 lb.
Height	4.156 in

Width	3.469 in
Dimensions	3 in x 3.469 in x 4.156 in

General

Conduit Type	Flexible Metal Conduit
Product Family	Flexible Metal
Insulation Type	Insulated
Fitting Type	Connectors
Product Type	Commercial Fittings
UPC	050169033104
Material	Malleable Iron

Logistics

Minimum Pack Quantity	1
Pallet Quantity	240
Carton Quantity	1

Product Assets

- [Catalog \[English\]](#)
- [Catalog \[English\]](#)
- [Catalog Page \[English\]](#)
- [Catalog Page \[English\]](#)