



3-1/2 in. Flex Straight Squeeze Connector, Insulated

By RACO
Catalog # 3314

3-1/2 in. Flex Straight Squeeze Connector, Insulated



Features

- All malleable construction ensures mechanical protection for the raceway
- Electro zinc plated for added corrosion protection
- UPC bar coded fittings are individually polybagged with a preprinted UPC-A bar code and packaged in pre-scored tear top cartons for an attractive presentation
- Additional sizes available

Specifications

Buy American Compliant	Contact Manufacturer
Certified Listed	cULus Listed
Buy America(n) Qualified	Contact Manufacturer

Configuration

Connector Type	Squeeze
----------------	---------

Dimensions

Length	5.203 in
Trade Size	3-1/2 in
Weight	4.464 lb.
Height	6.625 in

Width	4.688 in
Dimensions	5.203 in x 4.688 in x 6.625 in

General

Conduit Type	Flexible Metal Conduit
Product Family	Flexible Metal
Insulation Type	Insulated
Fitting Type	Connectors
Product Type	Commercial Fittings
UPC	050169033142
Material	Malleable Iron

Logistics

Minimum Pack Quantity	1
Pallet Quantity	252
Carton Quantity	1

Product Assets

- [Catalog \[English\]](#)
- [Catalog \[English\]](#)
- [Catalog Page \[English\]](#)
- [Catalog Page \[English\]](#)