



3 in. 90 Degree Liquidtight Connector, Uninsulated

By RACO
Catalog # 3432

3 in. 90 Degree Liquidtight Connector, Uninsulated

Features

- Use with flexible metallic liquidtight conduit and Type B flexible nonmetallic liquidtight conduit
- Zinc-electroplated for added corrosion protection
- Noninsulated
- Innovative split gland-ring assures a perfect seal, preventing pullouts
- Available in trade sizes 3/8 in. through 4 in.
- Sealing washer and heavy-duty locknut included
- All components are reusable

Specifications

Buy American Compliant Certified Listed	Contact Manufacturer • UL Listed • CSA Certified
Buy America(n) Qualified Industry Standard(s) Hazardous Rating(s)	Contact Manufacturer UL 514B • Class I, Division 2 • Class II Division 1 & 2 • Class III, Division 1 & 2

Dimensions

Length	4.75 in
Trade Size	3 in



Weight	8.35 lb.
Height	10.625 in
Width	4.75 in
Dimensions	4.75 in x 4.75 in x 10.625 in

General

Conduit Type	Liquidtight
Product Family	Liquidtight
Insulation Type	Uninsulated
Fitting Type	Connectors
Product Type	Commercial Fittings
UPC	050169034323
Material	Steel/Malleable Iron

Logistics

Minimum Pack Quantity	1
Pallet Quantity	192
Carton Quantity	1

Product Assets

- [Catalog \[English\]](#)
- [Catalog \[English\]](#)
- [Catalog Page \[English\]](#)
- [Catalog Page \[English\]](#)