



2-1/2 in. Liquidtight Straight Connector, Insulated with Ground Lug

By RACO
Catalog # 3520-3

2-1/2 in. Liquidtight Straight Connector, Insulated with Ground Lug

Features

- Malleable iron construction ensures mechanical protection
- All metallic components are zinc electroplated for added corrosion protection
- Insulated with ground lug
- Patented split gland-ring assures a perfect seal, preventing pullouts
- UL Listed, CSA
- Available in trade sizes 3/8 in. through 4 in.
- Sealing washer and heavy-duty locknut included
- All components are reusable

Specifications

Buy American Compliant Certified Listed	Contact Manufacturer • UL Listed • CSA Certified
Environmental Conditions	Wet Location
EU RoHS Indicator	Contact Manufacturer
Buy America(n) Qualified	Contact Manufacturer
Industry Standard(s)	UL 514B
Hazardous Rating(s)	• Class I, Division 2 • Class II Division 1 & 2 • Class III, Division 1 & 2

Configuration

Connector Type	Grounding
----------------	-----------

Current



Grounding Wire Capacity Maximum	#1/0 STR
Grounding Wire Capacity Minimum	#14 SOL
Dimensions	
Length	3.313 in
Trade Size	2-1/2 in
Weight	3.355 lb.
Height	3.625 in
Width	3.625 in
Dimensions	3.313 in x 3.625 in x 3.625 in

General

Conduit Type	Liquidtight
Insulation Type	Insulated
Fitting Type	Connectors
UPC	050169352038
Material	Steel/Malleable Iron

Logistics

Minimum Pack Quantity	1
Pallet Quantity	432
Carton Quantity	1

Product Assets

- [Catalog \[English\]](#)
- [Catalog \[English\]](#)
- [Catalog Page \[English\]](#)
- [Catalog Page \[English\]](#)