



2-1/2 in. Liquidtight Straight Connector, Insulated

By RACO
Catalog # [3520](#)

2-1/2 in. Liquidtight Straight Connector, Insulated

Features

- Use with flexible metallic liquidtight conduit and Type B flexible nonmetallic liquidtight conduit
- Zinc-electroplated for added corrosion protection
- Insulated
- Innovative split gland-ring assures a perfect seal, preventing pullouts
- Available in trade sizes 3/8 in. through 4 in.
- Sealing washer and heavy-duty locknut included
- All components are reusable

Specifications

Buy American Compliant	Contact Manufacturer
Certified Listed	• UL Listed • CSA Certified
Environmental Conditions	Wet Location
Buy America(n) Qualified	Contact Manufacturer
Industry Standard(s)	UL 514B
Hazardous Rating(s)	• Class I, Division 2 • Class II Division 1 & 2 • Class III, Division 1 & 2

Dimensions

Length	3.938 in
Trade Size	2-1/2 in



Weight	2.612 lb.
Height	3.563 in
Width	3.938 in
Dimensions	3.938 in x 3.938 in x 3.563 in

General

Conduit Type	Flexible Metal Conduit
Product Family	Liquidtight
Insulation Type	Insulated
Fitting Type	Connectors
Product Type	Commercial Fittings
UPC	050169035207
Material	Steel

Logistics

Minimum Pack Quantity	1
Pallet Quantity	972
Carton Quantity	1

Product Assets

- [Catalog \[English\]](#)
- [Catalog \[English\]](#)
- [Catalog Page \[English\]](#)
- [Catalog Page \[English\]](#)