



3 in. 90 Degree Liquidtight Connector, Insulated with Ground Lug

By RACO
Catalog # 3552-3

3 in. 90 Degree Liquidtight Connector, Insulated with Ground Lug

Features

- Malleable iron construction of the body and nut
- All metallic components are zinc electroplated for added corrosion protection
- Malleable iron castings mate with other components perfectly without strain or distortion
- Patented split gland-ring assures a perfect seal, preventing pullouts
- UL Listed, CSA
- Available in trade sizes 3/8 in. through 4 in.
- Sealing washer and heavy-duty locknut included
- All components are reusable

Specifications

Buy American Compliant	Contact Manufacturer
Certified Listed	cULus Listed
Environmental Conditions	Wet Location
EU RoHS Indicator	Contact Manufacturer
Buy America(n) Qualified	Contact Manufacturer
Industry Standard(s)	UL 514B

Configuration

Connector Type	Grounding
----------------	-----------

Dimensions



Length	7 in
Trade Size	3 in
Weight	6.869 lb.
Height	6.986 in
Width	4.407 in
Dimensions	7 in x 4.407 in x 6.986 in

General

Conduit Type	Liquidtight
Insulation Type	Insulated
Fitting Type	Connectors
UPC	050169355237
Material	Steel/Malleable Iron

Logistics

Minimum Pack Quantity	1
Pallet Quantity	200
Carton Quantity	1

Product Assets

- [Catalog \[English\]](#)
- [Catalog \[English\]](#)
- [Catalog Page \[English\]](#)
- [Catalog Page \[English\]](#)