Project / Job Name:

Location:

Fixture Type:

Notes:

65-725 - 15 Watt LED DOB Tempered Glass Flood Light; 4000K CCT; Bronze Finish

WET LOCATION · c UL us LISTED · FC · RoHS COMPLIANT · 30,000 HOURS · 120 VOLT · IP 65

GENERAL

Company	SATCO
EA Height	9.57
EA Width	8.27
EA Length	2.24
Bulb Included	Integrated
Material	Die-cast Aluminum
Fixture Type	Flood Light
Includes	Yoke Mount
Product Notes	NEMA Distribution: 6Vx6H (120x120)
Status	Active
Surge Protection	Built-in surge protection - 2KV
Total Harmonic Distortion	<30%
Up Down Installation	Up
CCT Selectable	No
Wattage Selectable	No
Finish Family	Bronze
Amps	0.130A
Integrated Features	Integrated Heat Sink For Thermal Management; 1/2 Inch Knuckle Mount
Lens Finish	Clear
Lens Material	Tempered Glass
Lensed	Yes
Power Factor	>0.94
SDS Class	LED_Fixture
Indoor Outdoor	Outdoor
Product Technology	LED
Incandescent Equivalent	75W

ELECTRICAL

CCT (Kelvin Temp)	4000K
Dimmable	Non-Dimmable
Hours Rated	30000
Beam Angle (degree)	120
Color Temp	Cool White
CRI	80+
Operating Frequency	50/60Hz
Operating Temp	-22F to +113F (-30C to +45C)
Lumens	1695L
Volts	120v
Watts	15W

PHYSICAL

Lamp Base	Integrated
Finish	BRONZE
ANSI Base	Integrated
Lamp Type	Integrated LED
Fixture Shape	Rectangle

ADDITIONAL INFO

Warranty	3-Years

FEATURES

Flicker Free	No

PACKAGING

UPC	045923410888
Case Cube	1.9317
Case Height	10.31
Case Length	17.13
Case Quantity	16
Case UPC	10045923410885
Case Weight	28.0
Case Width	18.9
EA Cube	0.1026
EA Height	9.57
EA Length	2.24
EA Quantity	1
EA Weight	1.63
EA Width	8.27
Pack Type	Color Box
Web Height	7.4
Web Length	1.02
Web Width	5.97

COMPLIANCE

ADA Compliant	No
Bug Rating	B1-U2-G1
CA Prop 65	Lead
Dark Sky Rated	No
FCC Compliant	Yes
IP Rating	IP65
Location Rating	Wet
NSF Approved	No
ROHS Compliant	Yes
Safety Listing	cULus - Certified, cULus - Listed
California Ban	Lawful for sale
DLC Approved	No
Title 20	Exempt
T24/JA8 Compliant	No

© Satco Products, Inc.
All rights reserved 2026