Project / Job Name:

Location:

Fixture Type:

Notes:

65-731 - 80 Watt LED DOB Tempered Glass Flood Light; 4000K CCT; Bronze Finish

WET LOCATION | c UL us LISTED | FC | RoHS COMPLIANT | 30,000 HOURS | 120 VOLT | IP 65

GENERAL

Company	SATCO
EA Height	11.57
EA Width	10.83
EA Length	2.24
Bulb Included	Integrated
Material	Die-cast Aluminum
Fixture Type	Flood Light
Includes	Yoke Mount
Product Notes	NEMA Distribution: 6Vx6H (120x120)
Status	Active
Surge Protection	Built-in surge protection - 2KV
Total Harmonic Distortion	<30%
Up Down Installation	Up
CCT Selectable	No
Wattage Selectable	No
Finish Family	Bronze
Amps	0.670A
Integrated Features	Integrated Heat Sink For Thermal Management; 1/2 Inch Knuckle Mount
Lens Finish	Clear
Lens Material	Tempered Glass
Lensed	Yes
Power Factor	>0.94
SDS Class	LED_Fixture
Indoor Outdoor	Outdoor
Product Technology	LED
Incandescent Equivalent	325W

ELECTRICAL

CCT (Kelvin Temp)	4000K
Dimmable	Non-Dimmable
Hours Rated	30000
Beam Angle (degree)	120
Color Temp	Cool White
CRI	80+
Operating Frequency	50/60Hz
Operating Temp	-22F to +113F (-30C to +45C)
Lumens	9040L
Volts	120v
Watts	80W

PHYSICAL

Lamp Base	Integrated
Finish	BRONZE
ANSI Base	Integrated
Lamp Type	Integrated LED
Fixture Shape	Rectangle

ADDITIONAL INFO

Warranty	3-Years

FEATURES

Flicker Free	No

PACKAGING

UPC	045923410970
Case Cube	1.4747
Case Height	11.34
Case Length	11.89
Case Quantity	8
Case UPC	10045923410977
Case Weight	22.46
Case Width	18.9
EA Cube	0.1624
EA Height	11.57
EA Length	2.24
EA Quantity	1
EA Weight	2.62
EA Width	10.83
Pack Type	Color Box
Web Height	9.17
Web Length	1.38
Web Width	8.33

COMPLIANCE

ADA Compliant	No
Bug Rating	B1-U2-G1
CA Prop 65	Lead
Dark Sky Rated	No
FCC Compliant	Yes
IP Rating	IP65
Location Rating	Wet
NSF Approved	No
ROHS Compliant	Yes
Safety Listing	cULus - Certified, cULus - Listed
California Ban	Lawful for sale
DLC Approved	No
Title 20	Exempt
T24/JA8 Compliant	No

© Satco Products, Inc.
All rights reserved 2026