Project / Job Name:

Location:

Fixture Type:

Notes:

**S11626R1** - 12 Watt LED Direct Wire Downlight; Gimbaled; 3.5 Inch; CCT Selectable; Round; Remote Driver; Brushed Nickel Finish; 840 Lumens; 120 Volt

## GENERAL

| | |
|---|---|
| Company | SATCO |
| EA Height | 5.31 |
| EA Width | 3.74 |
| EA Length | 5.31 |
| Bulb Included | Integrated |
| Diameter | 4.38 |
| Material | Aluminum |
| Fixture Type | Remote Driver LED Downlight |
| Status | Active |
| Style | Utility |
| Surge Protection | Built-in surge protection - 1.5KV |
| Total Harmonic Distortion | <30% |
| CCT Selectable | Yes |
| Wattage Selectable | No |
| Finish Family | Nickel |
| Additional Info | 360 Degree Rotation; 30 Degree Tilt |
| Amps | 0.100A |
| Has Camera | No |
| IOT Enabled | No |
| Lens Finish | Frost |
| Lens Material | Poly methyl methacrylate (PMMA) |
| Power Factor | >0.9 |
| SDS Class | LED_Lamp |
| Indoor Outdoor | Indoor, Outdoor |
| Product Technology | LED |
| Fixture Lamp Count | 1 |
| Incandescent Equivalent | 75W |

## ELECTRICAL

| | |
|---|---|
| CCT (Kelvin Temp) | 2700K/3000K/3500K/4000K/5000K |
| Dimmable | Yes-Dimmable |
| Hours Rated | 50000 |
| Beam Angle (degree) | 40 |
| Color Temp | Warm White to Natural Light |
| CRI | 90+ |
| Dimming Type | 120V only, Phase Cut (TRIAC) |
| Operating Frequency | 60Hz |
| Operating Temp | -4F to +113F (-20C to +45C) |
| Lumens | 840L |
| Volts | 120v |
| Watts | 12W |

## PHYSICAL

| | |
|---|---|
| Lamp Base | Integrated |
| Finish | Brushed Nickel |
| ANSI Base | Integrated |
| Lamp Type | Integrated LED |
| Fixture Shape | Round |

## ADDITIONAL INFO

| | |
|---|---|
| Warranty | 5-Years |

## PACKAGING

| | |
|---|---|
| UPC | 045923311291 |
| Case Cube | 0.9361 |
| Case Height | 11.61 |
| Case Length | 12.2 |
| Case Quantity | 12 |
| Case UPC | 10045923311298 |
| Case Weight | 14.69 |
| Case Width | 11.42 |
| EA Cube | 0.061 |
| EA Height | 5.31 |
| EA Length | 5.31 |
| EA Quantity | 1 |
| EA Weight | 1.15 |
| EA Width | 3.74 |
| Pack Type | Box |
| Web Height | 2.1 |
| Web Width | 4.38 |

## COMPLIANCE

| | |
|---|---|
| Air Tight | Yes |
| CA Prop 65 | Lead |
| FCC Compliant | Yes |
| IC Rated | Yes |
| Location Rating | Wet |
| ROHS Compliant | Yes |
| Safety Listing | cETLus - Listed |
| California Ban | California T24 Listed |
| DLC Approved | No |
| Energy Star Certified | No |
| Title 20 | Exempt |
| T24/JA8 Compliant | Yes |



© Satco Products, Inc.
All rights reserved 2026