Project / Job Name:

Location:

Fixture Type:

Notes:

S21414 - 18 Watt LED PL; CCT Selectable; Lumens Selectable; Type B; Ballast Bypass; White Finish; 120-277 Volt

GENERAL

Company	SATCO
EA Height	7.44
EA Width	2.36
EA Length	2.56
Lamp Ballast Type AB	Type B
Ballasting Requirements	Ballast Bypass; Direct wire 120-277V line voltage; No ballast or external driver required
Lamp Filament	LED
Material	Aluminum / Polycarbonate (PC)
Fixture Type	PL 2-Pin
Status	Active
Style	Transitional
Surge Protection	Built-in-surge protection - 0.5KV
Total Harmonic Distortion	20%
CCT Selectable	Yes
Wattage Selectable	No
Finish Family	White
Amps	0.150/0.065A
IOT Enabled	No
Minimum Compartment Size	Length: 6 in. Width: 6 in. Height: 8.5 in.
Operating Position	Universal
Power Factor	>0.9
SDS Class	LED_Lamp
Indoor Outdoor	Indoor, Outdoor
Product Technology	LED
Fluor Equiv	32W
Incandescent Equivalent	100W

ELECTRICAL

CCT (Kelvin Temp)	3000K/3500K/4000K/5000K/6500K
Dimmable	Non-Dimmable
Hours Rated	50000
Beam Angle (degree)	300
Color Temp	Warm White to Natural Light
CRI	80+
Operating Frequency	50/60Hz
Operating Temp	-13F to +122F (-25C to +50C)
Lumens	2250L-2340L
Volts	120V-277V
Watts	18W

PHYSICAL

Lamp Base	G24d (2-Pin)
Finish	WHITE
Housing Color	White
ANSI Base	G24d
Lamp Type	PL
MOD Lamps	1.95
MOL	6.12

ADDITIONAL INFO

Warranty	5-Years
Installation Notes	Suggested wattage equivalency = 32W CFL
Rated For Enclosed Fixture	Yes

PACKAGING

UPC	045923215735
Case Cube	0.7568
Case Height	15.75
Case Length	10.04
Case Quantity	24
Case UPC	10045923215732
Case Weight	12.58
Case Width	8.27
EA Cube	0.026
EA Height	7.44
EA Length	2.56
EA Quantity	1
EA Weight	0.52
EA Width	2.36
Pack Type	Box
Web Length	6.12
Web Width	1.95

COMPLIANCE

FCC Compliant	Yes
Location Rating	Damp
ROHS Compliant	Yes
Safety Listing	cRUus - Recognized Component, cULus - Certified, cULus - Classified
California Ban	Lawful for sale
DLC Approved	No
Title 20	Exempt
T24/JA8 Compliant	No

© Satco Products, Inc.
All rights reserved 2026