Project / Job Name:

Location:

Fixture Type:

Notes:

S29402 - 6.5 Watt; PAR20 LED; 3500K; 25 deg. Beam Angle; Medium base; 120 Volt

GENERAL

Company	SATCO
EA Height	3.54
EA Width	2.56
EA Length	2.56
Center Beam Candle Power	1179
Lamp Filament	LED
Material	Plastic
Fixture Type	PAR
Status	Active
Style	Utility
CCT Selectable	No
Wattage Selectable	No
Finish Family	Clear
Amps	0.054A
Has Camera	No
IOT Enabled	No
Lens Finish	Clear
Lens Material	Thermo Plastic (PBT)
Lensed	Yes
Operating Position	Universal
Photo Cell	No
Power Factor	0.9
SDS Class	LED_Lamp
Indoor Outdoor	Indoor, Outdoor
Product Technology	LED
Fluor Equiv	11W
Incandescent Equivalent	50W

ELECTRICAL

CCT (Kelvin Temp)	3500K
Dimmable	Yes-Dimmable
Hours Rated	25000
Beam Angle (degree)	25
Color Temp	Neutral White
CRI	90+
Dimming Type	120V only, Phase Cut (TRIAC)
Operating Frequency	60Hz
Operating Temp	-4F to +113F (-20C to +45C)
Lumens	520L
Volts	120v
Watts	6.5W

PHYSICAL

Lamp Base	Medium
Finish	Clear
Housing Color	Silver
ANSI Base	E26
Lamp Type	PAR20
MOD Lamps	2.44
MOL	2.99

ADDITIONAL INFO

Warranty	3-Years
Rated For Enclosed Fixture	Yes

PACKAGING

UPC	045923294020
Case Cube	0.5705
Case Height	9.06
Case Length	12.01
Case Quantity	24
Case UPC	10045923294027
Case Weight	5.88
Case Width	9.06
EA Cube	0.0134
EA Height	3.54
EA Length	2.56
EA Quantity	1
EA Weight	0.15
EA Width	2.56
Inner Cube	0.111
Inner Height	4.06
Inner Length	8.39
Inner Quantity	6
Inner UPC	20045923294024
Inner Weight	1.02
Inner Width	5.63
Pack Type	Box
Web Length	2.99
Web Width	2.44

COMPLIANCE

FCC Compliant	Yes
Location Rating	Wet
ROHS Compliant	Yes
Safety Listing	cULus - Listed
California Ban	California T24 Listed
DLC Approved	No
Title 20	Yes
T24/JA8 Compliant	Yes

© Satco Products, Inc.
All rights reserved 2026