Project / Job Name:

Location:

Fixture Type:

Notes:

S8448 - 32 Watt; T8; U-Bend Fluorescent; 4100K Cool White; 82 CRI; Medium Bi Pin base; 6-Pk

GENERAL

Company	SATCO
EA Height	7.28
EA Width	7.56
EA Length	23.43
Lamp Ballast Type AB	Type A
Ballasting Requirements	For use with Electronic ballasts
Fixture Type	U-Bend
Hg Content	7.5
Status	Active
CCT Selectable	No
Wattage Selectable	No
Finish Family	White
Has Camera	No
IOT Enabled	No
Leg Spacing	6.0
Lens Finish	White
Lensed	Yes
Mean Lumens	2700
Nominal Length	22.59
Operating Position	Universal
SDS Class	Linear_Fluorescent_Lamp
Product Technology	Fluorescent

ELECTRICAL

CCT (Kelvin Temp)	4100K
Dimmable	Non-Dimmable
Hours Rated	20000
Beam Angle (degree)	360
Color Temp	Cool White
CRI	80+
Operating Temp	Ballast Dependent
Lumens	3000L
Watts	32W

PHYSICAL

Lamp Base	Medium Bi Pin
Finish	WHITE
Housing Color	None
ANSI Base	G13
Lamp Type	T8
MOD Lamps	1.0
MOL	22.0

ADDITIONAL INFO

Warranty	3-Years

PACKAGING

UPC	045923084485
Case Cube	0.7443
Case Height	7.28
Case Length	23.62
Case Quantity	6
Case UPC	10045923084482
Case Weight	5.5
Case Width	7.48
EA Cube	0.7462
EA Height	7.28
EA Length	23.43
EA Quantity	1
EA Weight	5.0
EA Width	7.56
Pack Type	Box
Web Length	22.0
Web Width	1.0

COMPLIANCE

CA Prop 65	Lead
ROHS Compliant	Yes
Safety Listing	Not Applicable
California Ban	Non-Compliant
DLC Approved	No
Title 20	No
T24/JA8 Compliant	No
US State Ban	CA, CO, HI, ME, MN, OR, RI, VT

© Satco Products, Inc.
All rights reserved 2026