


Product data sheet

Specifications

Multi9 - comb busbar - 1L - 18 mm pitch - 12 modules - 100A



10285

Product availability: Stock - Normally stocked in distribution facility

Main

Range	Multi9
Product or Component Type	Comb busbar
Mounting Mode	Horizontal
Accessory / separate part category	Connection accessory
Lines description	1L
Length in 18 mm modules	12
Standards	UL 1077 CSA C22.2 No 235 EN/IEC 61439-1
Product certifications	CURus

Complementary

Number of ways	12 ways 1 L
Distribution type	L
Poles configuration for 1 way	1 x 1P
Connection pitch	0.7 in (18 mm)
Connector type	tooth
Distance between way	0.7 in (18 mm)
Marking	L
Insulation	Insulated
Device presentation	Uncuttable
[Ie] rated operational current	100 A 104 °F (40 °C)
[Ue] rated operational voltage	277 V AC Ph/N 480 V AC Ph/Ph
[Ui] rated insulation voltage	690 V AC
[Uimp] rated impulse withstand voltage	12 kV
Mounting location	Top tunnel type terminals
9 mm pitches	24
Width	8.5 in (216 mm)
color	Light gray RAL 7035)
Range compatibility	Multi9 C60SP

Environment

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Fire resistance	1760 °F (960 °C) 30 s)
-----------------	-------------------------

Ordering and shipping details

Category	US10DE200908
Discount Schedule	0DE2
GTIN	3303430102854
Returnability	Yes
Country of origin	DE

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	0.787 in (2.000 cm)
Package 1 Width	2.165 in (5.500 cm)
Package 1 Length	8.465 in (21.500 cm)
Package weight(Lbs)	2.787 oz (79.000 g)
Unit Type of Package 2	S02
Number of Units in Package 2	72
Package 2 Height	5.906 in (15.000 cm)
Package 2 Width	11.811 in (30.000 cm)
Package 2 Length	15.748 in (40.000 cm)
Package 2 Weight	13.098 lb(US) (5.941 kg)

Contractual warranty

Warranty (in months)	18
----------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



Environmental footprint

Total lifecycle Carbon footprint	1 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	0.4 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	0 kg CO2 eq.
Carbon footprint of the installation phase [A5]	0 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	0.4 kg CO2 eq.
Carbon footprint of the end-of-life phase [C1 to C4]	0.2 kg CO2 eq.
Environmental Disclosure	Product Environmental Profile

Use Better



Materials and Substances

Packaging made with recycled cardboard	No
Packaging without single use plastic	No
SCIP Number	12618b2a-bc0e-4c2d-bb7b-9185c26e01fe
EU RoHS Directive	Compliant
REACH Regulation	Reference contains Substances of Very High Concern above the threshold
California proposition 65	WARNING: This product can expose you to chemicals including: DINP, which is known to the State of California to cause cancer, and DIDP, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
PVC free	Yes

Use Longer



Lifetime extension

Repair	No
--------	----

Use Again



Repack and remanufacture

Recyclability potential, in %	67
Circularity Profile	No need of specific recycling operations
Take-back	No
WEEE Label	 The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

