

Product data sheet

Specifications



voltage release - MN - 48 V AC

26961

Product availability: Non-Stock - Not normally stocked in distribution facility

Main

range of product	Multi9
Product or Component Type	Undervoltage release
Device short name	MN
[Uc] control circuit voltage	48 V AC 50/60 Hz 48 V DC
Control Type	Standard
9 mm pitches	2

Complementary

Range compatibility	Multi9 C60 Multi9 N40 Acti9 iDPN
Local signalling	Action indicator
Mounting Mode	Fixed
Mounting Support	35 mm symmetrical DIN rail
Height	3.2 in (82.5 mm)
Width	0.7 in (18 mm)
Depth	2.7 in (68 mm)
Connections - terminals	Clamp terminal - 1 0.004 in² (2.5 mm²) - flexible Clamp terminal - 1 0.004 in² (2.5 mm²) - rigid Clamp terminal - 2 0.002 in² (1.5 mm²) - flexible Clamp terminal - 2 0.002 in² (1.5 mm²) - rigid
Wire stripping length	0.4 in (9 mm)
Tightening torque	8.9 lbf.in (1 N.m)

Environment

Standards	EN/IEC 60947-2
Product Certifications	ASEFA LCIE KEMA ASTA
Tropicalisation	2 EN/IEC 60947-2
Relative humidity	95 % 131 °F (55 °C)
Ambient Air Temperature for Operation	-13...122 °F (-25...50 °C)
Ambient Air Temperature for Storage	-40...185 °F (-40...85 °C)

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Ordering and shipping details

Category	US10DE201078
Discount Schedule	0DE2
GTIN	3303430269618
Returnability	No

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	3.5 in (9 cm)
Package 1 Width	0.9 in (2.4 cm)
Package 1 Length	3.1 in (8 cm)
Package weight(Lbs)	2.5 oz (70 g)
Unit Type of Package 2	BB1
Number of Units in Package 2	8
Package 2 Height	3.3 in (8.5 cm)
Package 2 Width	3.5 in (9 cm)
Package 2 Length	10.4 in (26.5 cm)
Package 2 Weight	22.2 oz (628 g)
Unit Type of Package 3	S03
Number of Units in Package 3	72
Package 3 Height	11.8 in (30 cm)
Package 3 Width	11.8 in (30 cm)
Package 3 Length	15.7 in (40 cm)
Package 3 Weight	13.534 lb(US) (6.139 kg)

Contractual warranty

Warranty	18 months
----------	-----------

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Better

 Materials and Substances	
Packaging made with recycled cardboard	No
Packaging without single use plastic	Yes
EU RoHS Directive	Compliant with Exemptions
SCIP Number	9da5f8d9-d60f-424a-bb30-a856a097686c
REACH Regulation	REACH Declaration
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov

Use Again

 Repack and remanufacture	
Take-back	No
WEEE Label	 The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.