


Product data sheet

Specifications



Standard opening voltage release
MX, ComPacT NS630b/NS3200,
fixed, 380/480VAC, spare part

33664

Product availability: Stock - Normally stocked in distribution facility

Main

Range	ComPacT
Range of Product	ComPacT NS630b...1600 new generation ComPacT NS1600b...3200 new generation
Device short name	MX
Product or Component Type	Voltage release
Device Application	Control
Voltage release type	Opening coil Instantaneous voltage release
Control Type	Standard
[Uc] control circuit voltage	380...480 V AC 50/60 Hz
Circuit breaker mounting mode	Fixed
Range compatibility	ComPact ComPact NS630b...1600 ComPact ComPact NS1600b...3200

Complementary

Operating threshold	0.7...1.1 x Un opening
Response time	50 ms +/- 10 % Compact NS630b...1600 50 ms +/- 10 % Compact NS1600b...3200 55 ms +/- 10 % MasterPact NT 70 ms +/- 10 % MasterPact NW
Supply holding power	4.5 VA
Accessory / separate part category	Spare part MasterPact NT Spare part MasterPact NW Spare part ComPacT NS630b...1600 new generation Spare part ComPacT NS1600b...3200 new generation

Ordering and shipping details

Category	US1DE2F01290
Discount Schedule	DE2F
GTIN	3303430336648
Returnability	No
Country of origin	FR

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	1.378 in (3.500 cm)

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Package 1 Width	2.362 in (6.000 cm)
Package 1 Length	3.268 in (8.300 cm)
Package weight(Lbs)	5.228 oz (148.200 g)
Unit Type of Package 2	BB1
Number of Units in Package 2	10
Package 2 Height	3.543 in (9.000 cm)
Package 2 Width	5.118 in (13.000 cm)
Package 2 Length	7.087 in (18.000 cm)
Package 2 Weight	3.380 lb(US) (1.533 kg)
Unit Type of Package 3	S03
Number of Units in Package 3	120
Package 3 Height	11.811 in (30.000 cm)
Package 3 Width	11.811 in (30.000 cm)
Package 3 Length	15.748 in (40.000 cm)
Package 3 Weight	40.089 lb(US) (18.184 kg)

Contractual warranty

Warranty (in months)	18
----------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



Environmental footprint

Total lifecycle Carbon footprint	3 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	3 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	0 kg CO2 eq.
Carbon footprint of the installation phase [A5]	0 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	0 kg CO2 eq.
Carbon footprint of the end-of-life phase [C1 to C4]	0.3 kg CO2 eq.
Environmental Disclosure	Product Environmental Profile

Use Better



Materials and Substances

Packaging made with recycled cardboard	Yes
Packaging without single use plastic	Yes
SCIP Number	Ad764790-535b-4a4e-825e-50fd804b5824
EU RoHS Directive	Compliant By Exemption
REACH Regulation	Reference contains Substances of Very High Concern above the threshold
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
Halogen content performance	Product contains halogen above thresholds
PVC free	Yes
Silicon free	Yes

Use Longer



Lifetime extension

Repair	No
--------	----

Use Again



Repack and remanufacture

Recyclability potential, in %	74
Circularity Profile	End of Life Information
Take-back	No



The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.