

Product data sheet

Specifications



MN delay unit, MasterPact NT/NW, ComPacT NS, adjustable time delay 0.5s to 3s, 48/60VDC, 48/60VAC 50/60Hz, spare part

33680

Product availability: Non-Stock - Not normally stocked in distribution facility

Main

Device short name	MN delay unit
Product or Component Type	Time delay relay
Device Application	Control
Range compatibility	Masterpact MasterPact NT Masterpact MasterPact NW ComPact ComPact NSX ComPact ComPact NS630b...1600 ComPact ComPact NS1600b...3200 PowerPact PowerPact Multistandard ComPact ComPact NSXm ComPact ComPact NSX DC Masterpact MasterPact NW UL 489 Masterpact MasterPact NT UL 489 Masterpact MasterPact NW DC
Voltage release type	Undervoltage release
[Uc] control circuit voltage	48...60 V AC 50/60 Hz 48...60 V DC

Complementary

Impulse duration	200 ms
Time delay range	0.5...3 s
Threshold tripping voltage	0.35...0.7 Un open 0.85 Un close
Supply holding power	4.5 VA
Supply inrush power	200 VA
Mounting Mode	External mounting
Response time	0.5 s 1 s 1.5 s 3 s
Accessory / separate part category	Spare part Compact NS630b...1600 Spare part Compact NS1600b...3200

Ordering and shipping details

Category	US1DE2F01291
Discount Schedule	DE2F
GTIN	3303430336808
Returnability	No

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Country of origin	FR
-------------------	----

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	3.3 in (8.4 cm)
Package 1 Width	3.0 in (7.6 cm)
Package 1 Length	3.5 in (9.0 cm)
Package weight(Lbs)	7.5 oz (214.0 g)
Unit Type of Package 2	S03
Number of Units in Package 2	18
Package 2 Height	11.8 in (30.0 cm)
Package 2 Width	11.8 in (30.0 cm)
Package 2 Length	15.7 in (40.0 cm)
Package 2 Weight	9.566 lb(US) (4.339 kg)

Contractual warranty

Warranty	18 months
----------	-----------

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Environmental footprint	
Carbon footprint (kg CO2 eq, Total Life cycle)	112
Environmental Disclosure	Product Environmental Profile

Use Better

Materials and Substances	
Packaging made with recycled cardboard	Yes
Packaging without single use plastic	Yes
EU RoHS Directive	Compliant with Exemptions
SCIP Number	6d7ed1bf-0416-4b0a-870a-811eb3730f6d
REACH Regulation	REACH Declaration
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
Halogen content performance	Product contains halogen above thresholds
PVC free	Yes

Use Again

Repack and remanufacture	
Circularity Profile	End of Life Information
Take-back	No
WEEE Label	 The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.