


Product data sheet

Specifications



Power distribution block, Linergy, 1 Pole, 2 line, 2 load, 760A Cu, 600V

9080LBC165212L

Product availability: Stock - Normally stocked in distribution facility

Main

Range	9080LB
Product	Power Distribution Block
Current Rating	760 A copper

Complementary

Voltage Rating	600 V AC/DC
Mounting Type	Surface mount
Number of poles	1
Terminals per Pole	2 line 12 load
Wire Size	2, AWG 4...500 kcmil, copper 12, AWG 14...AWG 2, copper
Terminal Tightening Torque	Line lug 375 lbf.in (42.4 N.m) AWG 4...500 kcmil copper Load lug 50 lbf.in (5.6 N.m) AWG 3...AWG 2 copper Load lug 45 lbf.in (5.08 N.m) AWG 6...AWG 4 copper Load lug 40 lbf.in (4.5 N.m) AWG 8 copper Load lug 35 lbf.in (4.0 N.m) AWG 14...AWG 10 copper Line lug 275 lbf.in (31.07 N.m) AWG 4...350 kcmil aluminium/copper Load lug 275 lbf.in (31.07 N.m) AWG 4...350 kcmil aluminium/copper
Wire stripping length	Line: 1.63 in (41.40 mm) for top connection Line: 1.63 in (41.40 mm) for bottom connection Load: 0.63 in (16.002 mm) for top connection Load: 1 in (25.4 mm) for bottom connection
Height	5.5 in (139.7 mm)
Width	2.88 in (73.15 mm)
Depth	3.92 in (99.57 mm)

Ordering and shipping details

Category	US10CP121711
Discount Schedule	0CP1
GTIN	3606487586999
Returnability	Yes
Country of origin	US

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	4.02 in (10.2 cm)

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Package 1 Width	10.0 in (25.4 cm)
Package 1 Length	22.008 in (55.9 cm)
Package weight(Lbs)	24.3 oz (689 g)

Contractual warranty

Warranty (in months)	18
----------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Better

Materials and Substances	
Packaging made with recycled cardboard	No
Packaging without single use plastic	No
EU RoHS Directive	Compliant
REACH Regulation	Free of Substances of Very High Concern above the threshold

Use Longer

Lifetime extension	
Repair	No

Use Again

Repack and remanufacture	
Take-back	No

Image of product / Alternate images

Alternative

